

Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014

		VRC-W 600 Premium
		204714
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, time control	kWh/(m ² p.a.)	-76.20
Specific energy consumption in average climates, time control	kWh/(m ² p.a.)	-38.30
Specific energy consumption in warmer climates, time control	kWh/(m ² p.a.)	-13.98
Energy efficiency class in colder climates, time control		A+
Energy efficiency class in average climates, time control		A
Energy efficiency class in warmer climates, time control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	87.6
Max. air flow rate	m ³ /h	600
Max. power consumption	W	251.8
Sound power level Lwa	dB(A)	54
Reference air flow rate	m ³ /s	0.117
Reference pressure differential	Pa	50
Specific input	W/(m ³ /h)	0.23
Control factor, time control		0,95
Declared maximum internal leakage rates	%	0,78
Declared maximum external leakage rates	%	0.59
Annual power consumption in colder climates with time control	kWh/a	842
Annual power consumption in average climates with time control	kWh/a	305
Annual power consumption in warmer climates with time control	kWh/a	260
Annual heating savings in colder climates with time control	kWh/a	8852
Annual heating savings in average climates with time control	kWh/a	4525
Annual heating savings in warmer climates with time control	kWh/a	2046