

		LWZ 8 CS Trend
Manufacturer	STIEBEL ELTRON	204859
Heat source	Luft	-
Low temperature heat pump	-	-
With auxiliary heater	-	-
Combination heater with heat pump	-	-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	11
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	7
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	8
T _j = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	6.4
T _j = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	5.9
T _j = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	3.9
T _j = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	3.5
T _j = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	8.3
T _j = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	2.8
T _j = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	2.7
T _j = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	5.4
T _j = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	3.2
T _j = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	3.2
T _j = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	3.2
T _j = dual mode temperature under colder climate conditions (Pdh)	kW	6.4
T _j = dual mode temperature under average climate conditions (Pdh)	kW	5.9
T _j = dual mode temperature under warmer climate conditions (Pdh)	kW	8.3
T _j = operating temperature limit under colder climate conditions (Pdh)	kW	2.6
T _j = operating temperature limit under average climate conditions (Pdh)	kW	2.7
T _j = operating temperature limit under warmer climate conditions (Pdh)	kW	8.3
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (Pdh)		-
Dual mode temperature under colder climate conditions (Tbiv)	Grad C	-7
Dual mode temperature under average climate conditions (Tbiv)	Grad C	-7
Dual mode temperature under warmer climate conditions (Tbiv)	Grad C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η _s)	%	102
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η _s)	%	128
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η _s)	%	150
T _j = -7 °C COP, partial load range under colder climate conditions (COPd)		2.5
T _j = -7 °C COP, partial load range under average climate conditions (COPd)		2.3
T _j = 2 °C COP, partial load range under colder climate conditions (COPd)		3.5
T _j = 2 °C COP, partial load range under average climate conditions (COPd)		3.3
T _j = 2 °C COP, partial load range under warmer climate conditions (COPd)		2.3
T _j = 7 °C COP, partial load range under colder climate conditions (COPd)		4.7
T _j = 7 °C COP, partial load range under average climate conditions (COPd)		4.1

T _j = 7 °C COP, partial load range under warmer climate conditions (COPd)	3.3	
T _j = 12 °C COP, partial load range under colder climate conditions (COPd)	5.7	
T _j = 12 °C COP, partial load range under average climate conditions (COPd)	5.3	
T _j = 12 °C COP, partial load range under warmer climate conditions (COPd)	5.1	
T _j = dual mode temperature under colder climate conditions (COPd)	2.5	
T _j = dual mode temperature under average climate conditions (COPd)	2.3	
T _j = dual mode temperature under warmer climate conditions (COPd)	2.3	
T _j = operating temperature limit under colder climate conditions (COPd)	2.1	
T _j = operating temperature limit under average climate conditions (COPd)	1.9	
T _j = operating temperature limit under warmer climate conditions (COPd)	2.3	
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (COPd)	-	
Operating temperature limit under colder climate conditions (TOL)	Grad C	-20
Operating temperature limit under average climate conditions (TOL)	Grad C	-10
Operating temperature limit under warmer climate conditions (TOL)	Grad C	2
Operating temperature limit of heating water under colder climate conditions (WTOL)	Grad C	60
Operating temperature limit of heating water under average climate conditions (WTOL)	Grad C	60
Operating temperature limit of heating water under warmer climate conditions (WTOL)	Grad C	60
Power consumption, off-mode (Poff)	Watt	27
Power consumption, thermostat off-mode (PTO)	Watt	63
Power consumption, standby state (PSB)	Watt	27
Power consumption, operating state, with crankcase heating (PCK)	Watt	35
Rated heating output of auxiliary heater under colder climate conditions (PSUP)	-	-
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	4
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)	-	-
Type of energy supply, auxiliary heater	elektrisch	
Output control	veränderlich	
Sound power level, outdoor	dB(A)	52
Sound power level, indoor	dB(A)	54
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	9932
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	4199
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	2911
Flow rate on heat source side	-	-
Load profile	-	-
Daily power consumption under colder climate conditions (QELEC)	-	-
Daily power consumption under average climate conditions (QELEC)	-	-
Daily power consumption under warmer climate conditions (QELEC)	-	-
Annual power consumption under colder climate conditions (AEC)	kWh	2042
Annual power consumption under average climate conditions (AEC)	kWh	1676
Annual power consumption under warmer climate conditions (AEC)	kWh	1183
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	-	-
Energy efficiency, DHW heating (η_{wh}), under average climate conditions	-	-
Energy efficiency, DHW heating (η_{wh}), warmer climates	-	-
Special measures	Alle beim Zusammenbau, der Installation oder Wartung des Raumheizgerätes zu treffenden besonderen Vorkehrungen: Siehe Installation- und Montageanweisung	