

Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014

		VRC-W 450 Premium
		204940
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, time control	kWh/(m ² p.a.)	-78.86
Specific energy consumption in average climates, time control	kWh/(m ² p.a.)	-40.35
Specific energy consumption in warmer climates, time control	kWh/(m ² p.a.)	-15.66
Energy efficiency class in colder climates, time control		A+
Energy efficiency class in average climates, time control		A
Energy efficiency class in warmer climates, time control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	89.7
Max. air flow rate	m ³ /h	450
Max. power consumption	W	131.9
Sound power level Lwa	dB(A)	49
Reference air flow rate	m ³ /s	0.087
Reference pressure differential	Pa	50
Specific input	W/(m ³ /h)	0.18
Control factor, time control		0.95
Declared maximum internal leakage rates	%	1.03
Declared maximum external leakage rates	%	0.78
Annual power consumption in colder climates with time control	kWh/a	785
Annual power consumption in average climates with time control	kWh/a	248
Annual power consumption in warmer climates with time control	kWh/a	203
Annual heating savings in colder climates with time control	kWh/a	8977
Annual heating savings in average climates with time control	kWh/a	4589
Annual heating savings in warmer climates with time control	kWh/a	2075