

## HPA-O 3 CS Plus compact D Set S 1.2

207653

Manufacturer	STIEBEL ELTRON	
Heat source	Luft	
Low temperature heat pump	-	
With auxiliary heater	-	
Combination heater with heat pump	-	
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	4
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	4
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	3
T <sub>j</sub> = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	2.7
T <sub>j</sub> = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	3.1
T <sub>j</sub> = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	1.6
T <sub>j</sub> = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	1.6
T <sub>j</sub> = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	3.1
T <sub>j</sub> = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	1.3
T <sub>j</sub> = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	1.3
T <sub>j</sub> = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	2
T <sub>j</sub> = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	1.5
T <sub>j</sub> = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	1.5
T <sub>j</sub> = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	1.5
T <sub>j</sub> = dual mode temperature under colder climate conditions (Pdh)	kW	3
T <sub>j</sub> = dual mode temperature under average climate conditions (Pdh)	kW	2.4
T <sub>j</sub> = dual mode temperature under warmer climate conditions (Pdh)	kW	3.1
T <sub>j</sub> = operating temperature limit under colder climate conditions (Pdh)	kW	2.6
T <sub>j</sub> = operating temperature limit under average climate conditions (Pdh)	kW	3.1
T <sub>j</sub> = operating temperature limit under warmer climate conditions (Pdh)	kW	3.1
For air source heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C) (Pdh)	kW	0
Dual mode temperature under colder climate conditions (Tbiv)	Grad C	-10
Dual mode temperature under average climate conditions (Tbiv)	Grad C	-5
Dual mode temperature under warmer climate conditions (Tbiv)	Grad C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η <sub>s</sub> )	%	102
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η <sub>s</sub> )	%	116
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η <sub>s</sub> )	%	137
T <sub>j</sub> = -7 °C COP, partial load range under colder climate conditions (COPd)		2.3
T <sub>j</sub> = -7 °C COP, partial load range under average climate conditions (COPd)		2.1
T <sub>j</sub> = 2 °C COP, partial load range under colder climate conditions (COPd)		3.5
T <sub>j</sub> = 2 °C COP, partial load range under average climate conditions (COPd)		2.9
T <sub>j</sub> = 2 °C COP, partial load range under warmer climate conditions (COPd)		2.2
T <sub>j</sub> = 7 °C COP, partial load range under colder climate conditions (COPd)		4.7
T <sub>j</sub> = 7 °C COP, partial load range under average climate conditions (COPd)		4.1

T <sub>j</sub> = 7 °C COP, partial load range under warmer climate conditions (COPd)		3.3
T <sub>j</sub> = 12 °C COP, partial load range under colder climate conditions (COPd)		6.7
T <sub>j</sub> = 12 °C COP, partial load range under average climate conditions (COPd)		6
T <sub>j</sub> = 12 °C COP, partial load range under warmer climate conditions (COPd)		5.2
T <sub>j</sub> = dual mode temperature under colder climate conditions (COPd)		2.1
T <sub>j</sub> = dual mode temperature under average climate conditions (COPd)		2.2
T <sub>j</sub> = dual mode temperature under warmer climate conditions (COPd)		2.2
T <sub>j</sub> = operating temperature limit under colder climate conditions (COPd)		2.3
T <sub>j</sub> = operating temperature limit under average climate conditions (COPd)		2.1
T <sub>j</sub> = operating temperature limit under warmer climate conditions (COPd)		2.2
For air source heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C) (COPd)		0
Operating temperature limit under colder climate conditions (TOL)	Grad C	-15
Operating temperature limit under average climate conditions (TOL)	Grad C	-5
Operating temperature limit under warmer climate conditions (TOL)	Grad C	2
Operating temperature limit of heating water under colder climate conditions (WTOL)		-
Operating temperature limit of heating water under average climate conditions (WTOL)	Grad C	60
Operating temperature limit of heating water under warmer climate conditions (WTOL)		-
Power consumption, off-mode (Poff)	Watt	17
Power consumption, thermostat off-mode (PTO)	Watt	30
Power consumption, standby state (PSB)	Watt	17
Power consumption, operating state, with crankcase heating (PCK)	Watt	5
Rated heating output of auxiliary heater under colder climate conditions (PSUP)		-
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	2.9
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)		-
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Sound power level, outdoor	dB(A)	52
Sound power level, indoor		-
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	4016
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	2089
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	1187
Flow rate on heat source side	m <sup>3</sup> /h	1300
Load profile		-
Daily power consumption under colder climate conditions (QELEC)		-
Daily power consumption under average climate conditions (QELEC)		-
Daily power consumption under warmer climate conditions (QELEC)		-
Annual power consumption under colder climate conditions (AEC)		-
Annual power consumption under average climate conditions (AEC)		-
Annual power consumption under warmer climate conditions (AEC)		-
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications ( $\eta_s$ )	%	200
Energy efficiency, DHW heating ( $\eta_{wh}$ ), under average climate conditions		-
Energy efficiency, DHW heating ( $\eta_{wh}$ ), warmer climates		-
Special measures	Alle beim Zusammenbau, der Installation oder Wartung des Raumheizgerätes zu treffenden besonderen Vorkehrungen: Siehe Installation- und Montageanweisung	