

LWZ 404 Trend		
		233255
Manufacturer		STIEBEL ELTRON
Heat source		-
Low temperature heat pump		-
With auxiliary heater		-
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	5
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	6
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	6
T _j = -7 °C heating output, partial load range under colder climate conditions (Pdh)		-
T _j = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	4.2
T _j = 2 °C heating output, partial load range under colder climate conditions (Pdh)		-
T _j = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	6.2
T _j = 2 °C heating output, partial load range under warmer climate conditions (Pdh)		-
T _j = 7 °C heating output, partial load range under colder climate conditions (Pdh)		-
T _j = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	7.3
T _j = 7 °C heating output, partial load range under warmer climate conditions (Pdh)		-
T _j = 12 °C heating output, partial load range under colder climate conditions (Pdh)		-
T _j = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	8.8
T _j = 12 °C heating output, partial load range under warmer climate conditions (Pdh)		-
T _j = dual mode temperature under colder climate conditions (Pdh)		-
T _j = dual mode temperature under average climate conditions (Pdh)	kW	4.7
T _j = dual mode temperature under warmer climate conditions (Pdh)		-
T _j = operating temperature limit under colder climate conditions (Pdh)		-
T _j = operating temperature limit under average climate conditions (Pdh)	kW	3.5
T _j = operating temperature limit under warmer climate conditions (Pdh)		-
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (Pdh)	kW	2.2
Dual mode temperature under colder climate conditions (Tbiv)		-
Dual mode temperature under average climate conditions (Tbiv)	Grad C	-5
Dual mode temperature under warmer climate conditions (Tbiv)		-
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	100
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	115
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	124
T _j = -7 °C COP, partial load range under colder climate conditions (COPd)		-
T _j = -7 °C COP, partial load range under average climate conditions (COPd)		2.3
T _j = 2 °C COP, partial load range under colder climate conditions (COPd)		-
T _j = 2 °C COP, partial load range under average climate conditions (COPd)		3.1
T _j = 2 °C COP, partial load range under warmer climate conditions (COPd)		-
T _j = 7 °C COP, partial load range under colder climate conditions (COPd)		-
T _j = 7 °C COP, partial load range under average climate conditions (COPd)		3.4

T_j = 7 °C COP, partial load range under warmer climate conditions (COPd)

T_j = 12 °C COP, partial load range under colder climate conditions (COPd)

T_j = 12 °C COP, partial load range under average climate conditions (COPd)

402

T_j = 12 °C COP, partial load range under warmer climate conditions (COPd)

T_j = dual mode temperature under colder climate conditions (COPd)

-

T_j = dual mode temperature under average climate conditions (COPd)

2.5

T_j = dual mode temperature under warmer climate conditions (COPd)

-

T_j = operating temperature limit under colder climate conditions (COPd)

-

T_j = operating temperature limit under average climate conditions (COPd)

2

T_j = operating temperature limit under warmer climate conditions (COPd)

-

For air source heat pumps: T_j = -15 °C (if TOL < -20 °C) (COPd)

1.4

Operating temperature limit under colder climate conditions (TOL)

-

Operating temperature limit under average climate conditions (TOL)

-

Operating temperature limit under warmer climate conditions (TOL)

-

Operating temperature limit of heating water under colder climate conditions (WTOL)

-

Operating temperature limit of heating water under average climate conditions (WTOL)

Grad C

0

Operating temperature limit of heating water under warmer climate conditions (WTOL)

-

Power consumption, off-mode (Poff)

Watt

12

Power consumption, thermostat off-mode (PTO)

Watt

82

Power consumption, standby state (PSB)

Watt

12

Power consumption, operating state, with crankcase heating (PCK)

Watt

12

Rated heating output of auxiliary heater under colder climate conditions (PSUP)

-

Rated heating output of auxiliary heater under average climate conditions (PSUP)

kW

2.3

Rated heating output of auxiliary heater under warmer climate conditions (PSUP)

-

Type of energy supply, auxiliary heater

-

Output control

-

Sound power level, outdoor

dB(A)

60

Sound power level, indoor

dB(A)

60

Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)

kWh/a

5155

Annual energy consumption under average climate conditions for medium-temperature applications (QHE)

kWh/a

4052

Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)

kWh/a

2567

Flow rate on heat source side

-

Load profile

XL

Daily power consumption under colder climate conditions (QELEC)

-

Daily power consumption under average climate conditions (QELEC)

-

Daily power consumption under warmer climate conditions (QELEC)

-

Annual power consumption under colder climate conditions (AEC)

-

Annual power consumption under average climate conditions (AEC)

-

Annual power consumption under warmer climate conditions (AEC)

-

Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)

-

Energy efficiency, DHW heating (η_{wh}), under average climate conditions

%

98

Energy efficiency, DHW heating (η_{wh}), warmer climates

-