

Manufacturer	STIEBEL ELTRON	
Heat source	-	
Low temperature heat pump	-	
With auxiliary heater	-	
Combination heater with heat pump	-	
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	-	
Rated heating output under average climate conditions for medium-temperature applications (P rated)	-	
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	-	
T _j = -7 °C heating output, partial load range under colder climate conditions (Pdh)	-	
T _j = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	8.6
T _j = 2 °C heating output, partial load range under colder climate conditions (Pdh)	-	
T _j = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	5.2
T _j = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	-	
T _j = 7 °C heating output, partial load range under colder climate conditions (Pdh)	-	
T _j = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	4.6
T _j = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	-	
T _j = 12 °C heating output, partial load range under colder climate conditions (Pdh)	-	
T _j = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	3.5
T _j = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	-	
T _j = dual mode temperature under colder climate conditions (Pdh)	-	
T _j = dual mode temperature under average climate conditions (Pdh)	kW	8
T _j = dual mode temperature under warmer climate conditions (Pdh)	-	
T _j = operating temperature limit under colder climate conditions (Pdh)	-	
T _j = operating temperature limit under average climate conditions (Pdh)	kW	9.4
T _j = operating temperature limit under warmer climate conditions (Pdh)	-	
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (Pdh)	kW	10.3
Dual mode temperature under colder climate conditions (Tbiv)	-	
Dual mode temperature under average climate conditions (Tbiv)	Grad C	-5
Dual mode temperature under warmer climate conditions (Tbiv)	-	
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	-	
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	-	
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	-	
T _j = -7 °C COP, partial load range under colder climate conditions (COPd)	-	
T _j = -7 °C COP, partial load range under average climate conditions (COPd)	kW	2.6
T _j = 2 °C COP, partial load range under colder climate conditions (COPd)	-	
T _j = 2 °C COP, partial load range under average climate conditions (COPd)	-	4.2
T _j = 2 °C COP, partial load range under warmer climate conditions (COPd)	-	
T _j = 7 °C COP, partial load range under colder climate conditions (COPd)	-	
T _j = 7 °C COP, partial load range under average climate conditions (COPd)	kW	6.2

T_j = 7 °C COP, partial load range under warmer climate conditions (COPd)

T_j = 12 °C COP, partial load range under colder climate conditions (COPd)

T_j = 12 °C COP, partial load range under average climate conditions (COPd)

3356

T_j = 12 °C COP, partial load range under warmer climate conditions (COPd)

T_j = dual mode temperature under colder climate conditions (COPd)

T_j = dual mode temperature under average climate conditions (COPd)

2.8

T_j = dual mode temperature under warmer climate conditions (COPd)

T_j = operating temperature limit under colder climate conditions (COPd)

T_j = operating temperature limit under average climate conditions (COPd)

2.5

T_j = operating temperature limit under warmer climate conditions (COPd)

For air source heat pumps: T_j = -15 °C (if TOL < -20 °C) (COPd)

2.3

Operating temperature limit under colder climate conditions (TOL)

Operating temperature limit under average climate conditions (TOL)

Operating temperature limit under warmer climate conditions (TOL)

Operating temperature limit of heating water under colder climate conditions (WTOL)

Operating temperature limit of heating water under average climate conditions (WTOL)

Grad C

60

Operating temperature limit of heating water under warmer climate conditions (WTOL)

Power consumption, off-mode (Poff)

Watt

24

Power consumption, thermostat off-mode (PTO)

Watt

69

Power consumption, standby state (PSB)

Watt

24

Power consumption, operating state, with crankcase heating (PCK)

Watt

55

Rated heating output of auxiliary heater under colder climate conditions (PSUP)

Rated heating output of auxiliary heater under average climate conditions (PSUP)

kW

0.5

Rated heating output of auxiliary heater under warmer climate conditions (PSUP)

Type of energy supply, auxiliary heater

Output control

Sound power level, outdoor

dB(A)

50

Sound power level, indoor

dB(A)

50

Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)

Annual energy consumption under average climate conditions for medium-temperature applications (QHE)

Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)

Flow rate on heat source side

Load profile

XL

Daily power consumption under colder climate conditions (QELEC)

Daily power consumption under average climate conditions (QELEC)

Daily power consumption under warmer climate conditions (QELEC)

Annual power consumption under colder climate conditions (AEC)

Annual power consumption under average climate conditions (AEC)

Annual power consumption under warmer climate conditions (AEC)

Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)

Energy efficiency, DHW heating (η_{wh}), under average climate conditions

Energy efficiency, DHW heating (η_{wh}), warmer climates