

		WPL 08 S Trend
		233871
Manufacturer		STIEBEL ELTRON
Heat source		Außenluft
Low temperature heat pump		-
With auxiliary heater		-
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	4
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	4
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	5
T _j = -7 °C heating output, partial load range under colder climate conditions (Pdh)		-
T _j = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	3.5
T _j = 2 °C heating output, partial load range under colder climate conditions (Pdh)		-
T _j = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	2.2
T _j = 2 °C heating output, partial load range under warmer climate conditions (Pdh)		-
T _j = 7 °C heating output, partial load range under colder climate conditions (Pdh)		-
T _j = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	2.2
T _j = 7 °C heating output, partial load range under warmer climate conditions (Pdh)		-
T _j = 12 °C heating output, partial load range under colder climate conditions (Pdh)		-
T _j = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	2.7
T _j = 12 °C heating output, partial load range under warmer climate conditions (Pdh)		-
T _j = dual mode temperature under colder climate conditions (Pdh)		-
T _j = dual mode temperature under average climate conditions (Pdh)	kW	4
T _j = dual mode temperature under warmer climate conditions (Pdh)		-
T _j = operating temperature limit under colder climate conditions (Pdh)		-
T _j = operating temperature limit under average climate conditions (Pdh)	kW	3.3
T _j = operating temperature limit under warmer climate conditions (Pdh)		-
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (Pdh)	kW	3.2
Dual mode temperature under colder climate conditions (Tbiv)		-
Dual mode temperature under average climate conditions (Tbiv)	Grad C	-10
Dual mode temperature under warmer climate conditions (Tbiv)		-
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)	%	130
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs)	%	139
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)	%	164
T _j = -7 °C COP, partial load range under colder climate conditions (COPd)		-
T _j = -7 °C COP, partial load range under average climate conditions (COPd)		2.1
T _j = 2 °C COP, partial load range under colder climate conditions (COPd)		-
T _j = 2 °C COP, partial load range under average climate conditions (COPd)		3.3
T _j = 2 °C COP, partial load range under warmer climate conditions (COPd)		-
T _j = 7 °C COP, partial load range under colder climate conditions (COPd)		-
T _j = 7 °C COP, partial load range under average climate conditions (COPd)		4.9

T_j = 7 °C COP, partial load range under warmer climate conditions (COPd)

T_j = 12 °C COP, partial load range under colder climate conditions (COPd)

T_j = 12 °C COP, partial load range under average climate conditions (COPd)

771

T_j = 12 °C COP, partial load range under warmer climate conditions (COPd)

T_j = dual mode temperature under colder climate conditions (COPd)

-

T_j = dual mode temperature under average climate conditions (COPd)

1.8

T_j = dual mode temperature under warmer climate conditions (COPd)

-

T_j = operating temperature limit under colder climate conditions (COPd)

-

T_j = operating temperature limit under average climate conditions (COPd)

1.6

T_j = operating temperature limit under warmer climate conditions (COPd)

-

For air source heat pumps: T_j = -15 °C (if TOL < -20 °C) (COPd)

1.8

Operating temperature limit under colder climate conditions (TOL)

-

Operating temperature limit under average climate conditions (TOL)

-

Operating temperature limit under warmer climate conditions (TOL)

-

Operating temperature limit of heating water under colder climate conditions (WTOL)

-

Operating temperature limit of heating water under average climate conditions (WTOL)

Grad C

60

Operating temperature limit of heating water under warmer climate conditions (WTOL)

-

Power consumption, off-mode (Poff)

Watt

17

Power consumption, thermostat off-mode (PTO)

Watt

17

Power consumption, standby state (PSB)

Watt

17

Power consumption, operating state, with crankcase heating (PCK)

Watt

26

Rated heating output of auxiliary heater under colder climate conditions (PSUP)

-

Rated heating output of auxiliary heater under average climate conditions (PSUP)

kW

0

Rated heating output of auxiliary heater under warmer climate conditions (PSUP)

-

Type of energy supply, auxiliary heater

elektrisch

Output control

veränderlich

Sound power level, outdoor

dB(A)

54

Sound power level, indoor

-

Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)

kWh/a

3059

Annual energy consumption under average climate conditions for medium-temperature applications (QHE)

kWh/a

2466

Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)

kWh/a

1819

Flow rate on heat source side

m³/h

4500