

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**

		<b>VRC-W 600 Premium</b>
		204714
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-78.27
Specific energy consumption in average climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-39.99
Specific energy consumption in warmer climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-15.44
Energy efficiency class in colder climates, central demand-dependent control		A+
Energy efficiency class in average climates, central demand-dependent control		A
Energy efficiency class in warmer climates, central demand-dependent control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	87.6
Max. air flow rate	m <sup>3</sup> /h	600
Max. power consumption	W	251.8
Sound power level L <sub>wa</sub>	dB(A)	54
Reference air flow rate	m <sup>3</sup> /s	0.117
Reference pressure differential	Pa	50
Specific input	W/(m <sup>3</sup> /h)	0.23
Control factor, central demand-dependent control		0.85
Declared maximum internal leakage rates	%	0.78
Declared maximum external leakage rates	%	0.59
Annual power consumption in colder climates with central demand-dependent control	kWh/a	790
Annual power consumption in average climates with central demand-dependent control	kWh/a	253
Annual power consumption in warmer climates with central demand-dependent control	kWh/a	208
Annual heating savings in colder climates with central demand-dependent control	kWh/a	8930
Annual heating savings in average climates with central demand-dependent control	kWh/a	4565
Annual heating savings in warmer climates with central demand-dependent control	kWh/a	2064