

Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014

		VRC-W 600 E Premium
		204715
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, manual control	kWh/(m ² p.a.)	-67.77
Specific energy consumption in average climates, manual control	kWh/(m ² p.a.)	-33.95
Specific energy consumption in warmer climates, manual control	kWh/(m ² p.a.)	-11.95
Energy efficiency class in colder climates, manual control		A+
Energy efficiency class in average climates, manual control		B
Energy efficiency class in warmer climates, manual control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	74.8
Max. air flow rate	m ³ /h	600
Max. power consumption	W	221.9
Sound power level Lwa	dB(A)	54
Reference air flow rate	m ³ /s	0.117
Reference pressure differential	Pa	50
Specific input	W/(m ³ /h)	0.21
Control factor, manual control		1
Declared maximum internal leakage rates	%	0,83
Declared maximum external leakage rates	%	0.59
Annual power consumption in colder climates with manual control	kWh/a	845
Annual power consumption in average climates with manual control	kWh/a	308
Annual power consumption in warmer climates with manual control	kWh/a	263
Annual heating savings in colder climates with manual control	kWh/a	8016
Annual heating savings in average climates with manual control	kWh/a	4572
Annual heating savings in warmer climates with manual control	kWh/a	1853