

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**

		<b>VRC-W 450 Premium</b>
		204940
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-80.52
Specific energy consumption in average climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-41.69
Specific energy consumption in warmer climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-16.83
Energy efficiency class in colder climates, central demand-dependent control		A+
Energy efficiency class in average climates, central demand-dependent control		A
Energy efficiency class in warmer climates, central demand-dependent control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	89.7
Max. air flow rate	m <sup>3</sup> /h	450
Max. power consumption	W	131.9
Sound power level L <sub>wa</sub>	dB(A)	49
Reference air flow rate	m <sup>3</sup> /s	0.087
Reference pressure differential	Pa	50
Specific input	W/(m <sup>3</sup> /h)	0.18
Control factor, central demand-dependent control		0.85
Declared maximum internal leakage rates	%	1,03
Declared maximum external leakage rates	%	0.78
Annual power consumption in colder climates with central demand-dependent control	kWh/a	745
Annual power consumption in average climates with central demand-dependent control	kWh/a	208
Annual power consumption in warmer climates with central demand-dependent control	kWh/a	163
Annual heating savings in colder climates with central demand-dependent control	kWh/a	9041
Annual heating savings in average climates with central demand-dependent control	kWh/a	4622
Annual heating savings in warmer climates with central demand-dependent control	kWh/a	2090