

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**

		<b>VRC-W 450 E Premium</b>
		204941
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, manual control	kWh/(m <sup>2</sup> p.a.)	-70.70
Specific energy consumption in average climates, manual control	kWh/(m <sup>2</sup> p.a.)	-36.22
Specific energy consumption in warmer climates, manual control	kWh/(m <sup>2</sup> p.a.)	-13.84
Energy efficiency class in colder climates, manual control		A+
Energy efficiency class in average climates, manual control		A
Energy efficiency class in warmer climates, manual control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	77
Max. air flow rate	m <sup>3</sup> /h	450
Max. power consumption	W	116.5
Sound power level Lwa	dB(A)	49
Reference air flow rate	m <sup>3</sup> /s	0.087
Reference pressure differential	Pa	50
Specific input	W/(m <sup>3</sup> /h)	0.16
Control factor, manual control		1
Declared maximum internal leakage rates	%	1,10
Declared maximum external leakage rates	%	0.78
Annual power consumption in colder climates with manual control	kWh/a	782
Annual power consumption in average climates with manual control	kWh/a	245
Annual power consumption in warmer climates with manual control	kWh/a	200
Annual heating savings in colder climates with manual control	kWh/a	8153
Annual heating savings in average climates with manual control	kWh/a	4168
Annual heating savings in warmer climates with manual control	kWh/a	1885