

WPL-A 10 HK Premium compact duo Set 1.2

207694

Manufacturer	STIEBEL ELTRON	
Heat source	Luft	
Low temperature heat pump	-	
With auxiliary heater	-	
Combination heater with heat pump	-	
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	15
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	11.6
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	10.1
T _j = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	9.1
T _j = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	10.2
T _j = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	6.7
T _j = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	7.1
T _j = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	10.1
T _j = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	7.9
T _j = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	8
T _j = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	8.7
T _j = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	9.1
T _j = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	9.3
T _j = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	9.1
T _j = dual mode temperature under colder climate conditions (Pdh)	kW	9.1
T _j = dual mode temperature under average climate conditions (Pdh)	kW	10.2
T _j = dual mode temperature under warmer climate conditions (Pdh)	kW	10.1
T _j = operating temperature limit under colder climate conditions (Pdh)	kW	8.7
T _j = operating temperature limit under average climate conditions (Pdh)	kW	10
T _j = operating temperature limit under warmer climate conditions (Pdh)	kW	10.1
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (Pdh)		-
Dual mode temperature under colder climate conditions (Tbiv)	Grad C	-7
Dual mode temperature under average climate conditions (Tbiv)	Grad C	-7
Dual mode temperature under warmer climate conditions (Tbiv)	Grad C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η _s)	%	118
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η _s)	%	135
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η _s)	%	159
T _j = -7 °C COP, partial load range under colder climate conditions (COPd)		2.7
T _j = -7 °C COP, partial load range under average climate conditions (COPd)		2.6
T _j = 2 °C COP, partial load range under colder climate conditions (COPd)		3.7
T _j = 2 °C COP, partial load range under average climate conditions (COPd)		3.3
T _j = 2 °C COP, partial load range under warmer climate conditions (COPd)		2.7
T _j = 7 °C COP, partial load range under colder climate conditions (COPd)		4.6
T _j = 7 °C COP, partial load range under average climate conditions (COPd)		4.2

T _j = 7 °C COP, partial load range under warmer climate conditions (COPd)	3.6	
T _j = 12 °C COP, partial load range under colder climate conditions (COPd)	5.5	
T _j = 12 °C COP, partial load range under average climate conditions (COPd)	5.2	
T _j = 12 °C COP, partial load range under warmer climate conditions (COPd)	5	
T _j = dual mode temperature under colder climate conditions (COPd)	2.7	
T _j = dual mode temperature under average climate conditions (COPd)	2.6	
T _j = dual mode temperature under warmer climate conditions (COPd)	2.7	
T _j = operating temperature limit under colder climate conditions (COPd)	2	
T _j = operating temperature limit under average climate conditions (COPd)	2.3	
T _j = operating temperature limit under warmer climate conditions (COPd)	2.7	
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (COPd)	-	
Operating temperature limit under colder climate conditions (TOL)	Grad C	-20
Operating temperature limit under average climate conditions (TOL)	Grad C	-10
Operating temperature limit under warmer climate conditions (TOL)	Grad C	2
Operating temperature limit of heating water under colder climate conditions (WTOL)	Grad C	65
Operating temperature limit of heating water under average climate conditions (WTOL)	Grad C	65
Operating temperature limit of heating water under warmer climate conditions (WTOL)	Grad C	65
Power consumption, off-mode (Poff)	Watt	10
Power consumption, thermostat off-mode (PTO)	Watt	10
Power consumption, standby state (PSB)	Watt	10
Power consumption, operating state, with crankcase heating (PCK)	Watt	38
Rated heating output of auxiliary heater under colder climate conditions (PSUP)	kW	15
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	1.6
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)	kW	0
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Sound power level, outdoor	dB(A)	55
Sound power level, indoor		-
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	12237
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	6969
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	3330
Flow rate on heat source side	m ³ /h	4000
Load profile		-
Daily power consumption under colder climate conditions (QELEC)		-
Daily power consumption under average climate conditions (QELEC)		-
Daily power consumption under warmer climate conditions (QELEC)		-
Annual power consumption under colder climate conditions (AEC)		-
Annual power consumption under average climate conditions (AEC)		-
Annual power consumption under warmer climate conditions (AEC)		-
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	%	200
Energy efficiency, DHW heating (η_{wh}), under average climate conditions		-
Energy efficiency, DHW heating (η_{wh}), warmer climates		-