

**Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)**

|   |    | <b>WPL 24 A SR Set</b> |
|---|----|------------------------|
|   |    | 236415                 |
| Manufacturer  |    | STIEBEL ELTRON         |
| Heat source   |    | Luft                   |
| Low temperature heat pump   |    | -                      |
| With auxiliary heater   |    | x                      |
| Combination heater with heat pump   |    | -                      |
| Rated heating output under colder climate conditions for medium-temperature applications (P rated)                              | kW | 19                     |
| Rated heating output under average climate conditions for medium-temperature applications (P rated)                             | kW | 16                     |
| Rated heating output under warmer climate conditions for medium-temperature applications (P rated)                              | kW | 10                     |
| T <sub>j</sub> = -7 °C heating output, partial load range under colder climate conditions (Pdh)                                 | kW | 14,0                   |
| T <sub>j</sub> = -7 °C heating output, partial load range under average climate conditions (Pdh)                                | kW | 15,0                   |
| T <sub>j</sub> = 2 °C heating output, partial load range under colder climate conditions (Pdh)                                  | kW | 10,0                   |
| T <sub>j</sub> = 2 °C heating output, partial load range under average climate conditions (Pdh)                                 | kW | 10,0                   |
| T <sub>j</sub> = 2 °C heating output, partial load range under warmer climate conditions (Pdh)                                  | kW | 11,0                   |
| T <sub>j</sub> = 7 °C heating output, partial load range under colder climate conditions (Pdh)                                  | kW | 8,0                    |
| T <sub>j</sub> = 7 °C heating output, partial load range under average climate conditions (Pdh)                                 | kW | 8,0                    |
| T <sub>j</sub> = 7 °C heating output, partial load range under warmer climate conditions (Pdh)                                  | kW | 10,0                   |
| T <sub>j</sub> = 12 °C heating output, partial load range under colder climate conditions (Pdh)                                 | kW | 8,0                    |
| T <sub>j</sub> = 12 °C heating output, partial load range under average climate conditions (Pdh)                                | kW | 8,0                    |
| T <sub>j</sub> = 12 °C heating output, partial load range under warmer climate conditions (Pdh)                                 | kW | 8,0                    |
| T <sub>j</sub> = dual mode temperature under colder climate conditions (Pdh)  | kW | 15,0                   |
| T <sub>j</sub> = dual mode temperature under average climate conditions (Pdh)   | kW | 15,0                   |
| T <sub>j</sub> = dual mode temperature under warmer climate conditions (Pdh)  | kW | 11,0                   |
| T <sub>j</sub> = operating temperature limit under colder climate conditions (Pdh)  | kW | 12,0                   |
| T <sub>j</sub> = operating temperature limit under average climate conditions (Pdh)   | kW | 12,0                   |
| T <sub>j</sub> = operating temperature limit under warmer climate conditions (Pdh)  | kW | 11,0                   |
| For air source heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C) (Pdh)  | kW | 0,0                    |
| Dual mode temperature under colder climate conditions (T <sub>biv</sub> )   | °C | -7                     |
| Dual mode temperature under average climate conditions (T <sub>biv</sub> )  | °C | -7                     |
| Dual mode temperature under warmer climate conditions (T <sub>biv</sub> )   | °C | 2                      |
| Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η <sub>s</sub> )  | %  | 127                    |
| Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η <sub>s</sub> ) | %  | 138                    |
| Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η <sub>s</sub> )  | %  | 157                    |
| T <sub>j</sub> = -7 °C COP, partial load range under colder climate conditions (COP <sub>d</sub> )                              |    | 3,00                   |
| T <sub>j</sub> = -7 °C COP, partial load range under average climate conditions (COP <sub>d</sub> )                             |    | 3,00                   |
| T <sub>j</sub> = 2 °C COP, partial load range under colder climate conditions (COP <sub>d</sub> )                               |    | 4,00                   |
| T <sub>j</sub> = 2 °C COP, partial load range under average climate conditions (COP <sub>d</sub> )                              |    | 4,00                   |
| T <sub>j</sub> = 2 °C COP, partial load range under warmer climate conditions (COP <sub>d</sub> )                               |    | 3,00                   |
| T <sub>j</sub> = 7 °C COP, partial load range under colder climate conditions (COP <sub>d</sub> )                               |    | 6,00                   |
| T <sub>j</sub> = 7 °C COP, partial load range under average climate conditions (COP <sub>d</sub> )                              |    | 5,00                   |

|  |                   |              |
|--|-------------------|--------------|
| Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)                             |                   | 4,00         |
| Tj = 12 °C COP, partial load range under colder climate conditions (COPd)                            |                   | 7,00         |
| Tj = 12 °C COP, partial load range under average climate conditions (COPd)                           |                   | 7,00         |
| Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)                            |                   | 6,00         |
| Tj = dual mode temperature under colder climate conditions (COPd)                                    |                   | 2,00         |
| Tj = dual mode temperature under average climate conditions (COPd)                                   |                   | 3,00         |
| Tj = dual mode temperature under warmer climate conditions (COPd)                                    |                   | 3,00         |
| Tj = operating temperature limit under colder climate conditions (COPd)                              |                   | 3,00         |
| Tj = operating temperature limit under average climate conditions (COPd)                             |                   | 2,00         |
| For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)                                      |                   | 0,00         |
| Operating temperature limit of heating water under average climate conditions (WTOL)                 | °C                | 65           |
| Power consumption, off-mode (Poff)   | W                 | 25           |
| Power consumption, thermostat off-mode (PTO)   | W                 | 25           |
| Power consumption, standby state (PSB)   | W                 | 25           |
| Power consumption, operating state, with crankcase heating (PCK)                                     | W                 | 0            |
| Rated heating output of auxiliary heater under average climate conditions (PSUP)                     | kW                | 5,0          |
| Type of energy supply, auxiliary heater  |                   | elektrisch   |
| Output control   |                   | veränderlich |
| Sound power level, outdoor   | dB(A)             | 46           |
| Sound power level, indoor  | dB(A)             | 54           |
| Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)  | kWh/a             | 14103        |
| Annual energy consumption under average climate conditions for medium-temperature applications (QHE) | kWh/a             | 9475         |
| Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)  | kWh/a             | 3373         |
| Flow rate on heat source side  | m <sup>3</sup> /h | 2300         |