



ENERG Y IJA
 енергия · ενεργεια IE IA

STIEBEL ELTRON

HPA-O 6 CS Plus hybrid
 Set



55 °C

35 °C



A+

A++

57 dB

■ 7	■ 6
■ 7	■ 7
■ 7	■ 6
kW	kW

2019

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		HPA-O 6 CS Plus hybrid Set
		201603
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Rated heating output in moderate climates for average temperature applications (Prated)	kW	7
Rated heating output in moderate climates for low temperature applications (Prated)	kW	7
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	124
Seasonal room heating efficiency in moderate climates for low temperature applications (η_s)	%	182
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	4917
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	3038
Sound power level external	dB(A)	57
Rated heating output in colder climates for average temperature applications (Prated)	kW	7
Rated heating output in colder climates for low temperature applications (Prated)	kW	6
Rated heating output in warmer climates for average temperature applications (Prated)	kW	7
Rated heating output in warmer climates for low temperature applications (Prated)	kW	6
Seasonal room heating efficiency in colder climates for average temperature applications (η_s)	%	112
Seasonal room heating efficiency in colder climates for low temperature applications (η_s)	%	153
Seasonal room heating efficiency in warmer climates for average temperature applications (η_s)	%	160
Seasonal room heating efficiency in warmer climates for low temperature applications (η_s)	%	217
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	5564
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	3675
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2128
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	1533



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

HPA-O 6 CS Plus hybrid Set






+ 
 + 
 + 
 + 


 









Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		HPA-O 6 CS Plus hybrid Set
		201603
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	124
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	128
Room heating energy efficiency of composite system under colder climatic conditions	%	116
Room heating energy efficiency of composite system under warmer climatic conditions	%	164
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	12
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	36
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		HPA-O 6 CS Plus hybrid Set
		201603
Manufacturer		STIEBEL ELTRON
Heat source		Outside air
Low temperature heat pump		-
With booster heater		-
Combi boiler with heat pump		-
Rated heating output in colder climates for average temperature applications (Prated)	kW	7
Rated heating output in moderate climates for average temperature applications (Prated)	kW	7
Rated heating output in warmer climates for average temperature applications (Prated)	kW	7
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	6,02
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	3,66
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	3,5
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	3,39
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	6,5
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	6,3
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	0
Dual mode temperature in moderate climates (Tbiv)	°C	-7
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	112
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	124
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	160
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,9
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		4,5
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		6,6
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		6,78
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,9
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,8
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		0
Heating water operating temperature limit (WTOL)	°C	60
Power consumption, OFF state (Poff)	W	17
Power consumption, thermostat OFF state (PTO)	W	30
Standby power consumption (PSB)	W	17
Power consumption, operating state, with crankcase heating (PCK)	W	5
Booster heater heating output (PSUB)	kW	0,5
Type of energy supply, booster heater		electric
Power control		variable
Sound power level external	dB(A)	57
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	5564
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	4917
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2128
Flow rate, heat source side	m³/h	2200