

### Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		HPA-O 24 Trend CN
		202199
Manufacturer		STIEBEL ELTRON
Space heating energy efficiency class under average climate conditions, medium- temperature applications		A+
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	33
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	31
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications ( $\ensuremath{\eta}s$ )	%	110
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\ensuremath{\Pi}s$ )	%	134
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	24031
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	18707
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	34
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	32
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	31
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	30
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications ( $\ensuremath{\eta}s\xspace$	%	92
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications ( $\ensuremath{\eta}s\xspace$ )	%	108
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications ( $\boldsymbol{\eta}s$ )	%	108
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications ( $\ensuremath{\eta}s$ )	%	133
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	35394
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	28347
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	14885
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	11817
Sound power level, outdoor	dB(A)	69





#### HPA-O 24 Trend CN

# STIEBEL ELTRON

# 



## Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		HPA-O 24 Trend CN
		202199
Manufacturer		STIEBEL ELTRON
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (ηs)	%	134
Temperature control class		VII
Contribution of temperature control to space heating energy efficiency	%	4
Space heating energy efficiency of package under average climate conditions	%	113
Space heating energy efficiency of package under colder climate conditions	%	95
Space heating energy efficiency of package under warmer climate conditions	%	111
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	9
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	16
Energy efficiency class, space heating under average climate conditions, low-temperature applications		Α+
Space heating energy efficiency class of package under average climate conditions		Α+

### Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		HPA-O 24 Trend CN	
Manufacturer		STIEREL ELTRON	
Heat source		Außenluft	
With auxiliary heater	·	-	
Combination heater with heat pump		-	
Rated heating output under colder climate conditions for medium- temperature applications (P rated)	kW	34	
Rated heating output under average climate conditions for medium- temperature applications (P rated)	kW	33	
Rated heating output under warmer climate conditions for medium- temperature applications (P rated)	kW	31	
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	24,9	
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	25,5	
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	30,3	
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	30,5	
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	31,2	
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	30,8	
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	30,7	
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	30,3	
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	38,9	
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	38,7	
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	38,4	
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	23,1	
Tj = dual mode temperature under average climate conditions (Pdh)	kW	26,5	
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	31,2	
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	17,7	
Tj = operating temperature limit under average climate conditions (Pdh)	kW	23,9	
$T_j = operating temperature limit under warmer climate conditions (Pdh)$	kW	31,2	
For air source heat pumps: Ij = -15 °C (if IOL< -20 °C) (Pdh)	<u>kW</u>	21,4	
Dual mode temperature under colder climate conditions (Tbiv)	<u></u>	-10	
Dual mode temperature under warmer climate conditions (Tbiv)	<u> </u>	c- د	
Seasonal space beating energy efficiency under colder climate	<u> </u>	2	
conditions for medium-temperature applications (\ns)	%	92	
conditions for medium-temperature applications (Ŋs)	%	110	
conditions for medium-temperature applications ( $\eta$ s)	%	108	
(COPd)		2,48	
(COPd)		2,30	
$IJ = 2 \degree C COP$ , partial load range under colder climate conditions (COPd)		2,98	
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		2,84	
IJ = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,53	
$IJ = 7 \degree C COP$ , partial load range under colder climate conditions (COPd)		3,40	
IJ = 7 °C COP, partial load range under average climate conditions (COPd)		3,24	
(COPd)		2,90	

Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		4,16
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		405,00
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		3,87
Tj = dual mode temperature under colder climate conditions (COPd)		2,32
Tj = dual mode temperature under average climate conditions (COPd)		2,43
Tj = dual mode temperature under warmer climate conditions (COPd)		2,53
Tj = operating temperature limit under colder climate conditions (COPd)		1,73
Tj = operating temperature limit under average climate conditions (COPd)		2,12
Tj = operating temperature limit under warmer climate conditions (COPd)		2,53
For air source heat pumps: Tj = -15 °C (if TOL< -20 °C) (COPd)		1,84
Operating temperature limit under colder climate conditions (TOL)	°C	-20
Operating temperature limit under average climate conditions (TOL)	°C	-10
Operating temperature limit under warmer climate conditions (TOL)	°C	2
Operating temperature limit of heating water under colder climate conditions (WTOL)	°C	60
Operating temperature limit of heating water under average climate conditions (WTOL)	°C	60
Operating temperature limit of heating water under warmer climate conditions (WTOL)	°C	60
Power consumption, off-mode (Poff)	W	7
Power consumption, thermostat off-mode (PTO)	W	7
Power consumption, standby state (PSB)	W	7
Power consumption, operating state, with crankcase heating (PCK)	W	25
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	9,1
Type of energy supply, auxiliary heater		elektrisch
Output control		fest
Sound power level, outdoor	dB(A)	69
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	35394
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	24031
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	14885
Flow rate on heat source side	m³/h	7300