



ENERG
енергия · ενέργεια

Y IJA
IE IA

STIEBEL ELTRON WPL 33 HT



55 °C

35 °C



A+

A+

53 dB

58 dB

■ 21	■ 20
■ 14	■ 14
■ 8	■ 7
kW	kW

2019

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		WPL 33 HT
		229938
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A+
Rated heating output in moderate climates for average temperature applications (Prated)	kW	14
Rated heating output in moderate climates for low temperature applications (Prated)	kW	14
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	122
Seasonal room heating efficiency in moderate climates for low temperature applications (η_s)	%	147
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	9557
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	7663
Sound power level internal	dB(A)	53
Sound power level external	dB(A)	58
Rated heating output in colder climates for average temperature applications (Prated)	kW	21
Rated heating output in colder climates for low temperature applications (Prated)	kW	20
Rated heating output in warmer climates for average temperature applications (Prated)	kW	8
Rated heating output in warmer climates for low temperature applications (Prated)	kW	7
Seasonal room heating efficiency in colder climates for average temperature applications (η_s)	%	92
Seasonal room heating efficiency in colder climates for low temperature applications (η_s)	%	110
Seasonal room heating efficiency in warmer climates for average temperature applications (η_s)	%	163
Seasonal room heating efficiency in warmer climates for low temperature applications (η_s)	%	183
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	22302
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	17781
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2907
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	2489



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

WPL 33 HT






+ 
 + 
 + 
 + 


 









Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		WPL 33 HT
		229938
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	122
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	126
Room heating energy efficiency of composite system under colder climatic conditions	%	96
Room heating energy efficiency of composite system under warmer climatic conditions	%	167
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	30
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	41
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		WPL 33 HT
		229938
Manufacturer		STIEBEL ELTRON
Heat source		Outside air
Low temperature heat pump		-
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in colder climates for average temperature applications (Prated)	kW	21
Rated heating output in moderate climates for average temperature applications (Prated)	kW	14
Rated heating output in warmer climates for average temperature applications (Prated)	kW	8
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	12,8
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	7,6
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	5,6
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	6,6
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	11,7
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	13,8
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	14,34
Dual mode temperature in moderate climates (Tbiv)	°C	-5
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	92
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	122
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	163
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,09
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,06
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4,32
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		5,79
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,31
Tj = operating temperature limit under moderate climatic conditions (COPd)		1,51
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		2,11
Heating water operating temperature limit (WTOL)	°C	75
Power consumption, OFF state (Poff)	W	7
Power consumption, thermostat OFF state (PTO)	W	7
Standby power consumption (PSB)	W	7
Power consumption, operating state, with crankcase heating (PCK)	W	62
Booster heater heating output (PSUB)	kW	0,64
Type of energy supply, booster heater		electric
Power control		Fixed
Sound power level external	dB(A)	58
Sound power level internal	dB(A)	53
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	22302
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	9557
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2907
Flow rate, heat source side	m ³ /h	3500