



**ENERG**  
енергия · ενέργεια

Y IJA  
IE IA

**STIEBEL ELTRON** WPL 10 AC



55 °C

35 °C



A+

A+

59 dB

■ 6	■ 7
■ 6	■ 7
■ 5	■ 7
kW	kW

2015

812/2013

		<b>WPL 10 AC</b>
		230236
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A+
Rated heating output in moderate climates for medium temperature applications	kW	6
Rated heating output in moderate climates for low temperature applications	kW	7
Energy efficiency for central heating in moderate climates for medium temperature applications	%	115
Energy efficiency for central heating in moderate climates for low temperature applications	%	146
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	4007
Energy consumption for central heating under moderate climatic conditions, for low temperature applications	kWh/a	3837
Rated heating output in colder climates for medium temperature applications	kW	6
Rated heating output in colder climates for low temperature applications	kW	7
Rated heating output in warmer climates for medium temperature applications	kW	5
Rated heating output in warmer climates for low temperature applications	kW	7
Energy efficiency for central heating in colder climates for medium temperature applications	%	106
Energy efficiency for central heating in colder climates for low temperature applications	%	129
Energy efficiency for central heating in warmer climates for medium temperature applications	%	132
Energy efficiency for central heating in warmer climates for low temperature applications	%	169
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	5266
Energy consumption for central heating under colder climatic conditions, for low temperature applications	kWh/a	5219
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	2136
Energy consumption for central heating under warmer climatic conditions, for low temperature applications	kWh/a	2095
Sound power level external	dB(A)	59



# ENERG

енергия · ενεργεια

Y

IJA

IE

IA






**STIEBEL ELTRON**

WPL 10 AC






+    
 +    
 +    
 + 

		<b>WPL 10 AC</b>
		230236
Manufacturer		STIEBEL ELTRON
Energy efficiency for central heating in moderate climates for medium temperature applications	%	115
Temperature controller class		VII
Contribution of temperature controller to room heating energy efficiency	%	3,5
Room heating energy efficiency of composite system under moderate climatic conditions	%	119
Room heating energy efficiency of composite system under colder climatic conditions	%	110
Room heating energy efficiency of composite system under warmer climatic conditions	%	136
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	9
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	17
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A+

		<b>WPL 10 AC</b>
		230236
Manufacturer		STIEBEL ELTRON
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in moderate climates for medium temperature applications	kW	6
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	5,2
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	6,9
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	8,0
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	10,5
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	5,6
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	4,6
For air/water heat pumps:Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	3,6
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		3,10
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,72
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4,14
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		5,09
Tj = dual mode temperature under moderate climatic conditions (COPd)		3,26
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,88
For air/water heat pumps:Tj = -15 °C (if TOL < -20 °C) (COPd)		2,50
Dual mode temperature (Tbiv)	°C	-5
Heating water operating temperature limit (WTOL)	°C	60
Power consumption, OFF state (Poff)	W	5
Power consumption, thermostat OFF state (PTO)	W	5
Standby power consumption (PSB)	W	5
Power consumption, operating state, with crankcase heating (PCK)	W	60
Booster heater heating output (PSUB)	kW	2,34
Type of energy supply, booster heater		electric
Power control		Fixed
Sound power level external	dB(A)	59
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	4007
Flow rate, heat source side	m <sup>3</sup> /h	2300