



ENERG Y IJA
 енергия · ενέργεια IE IA

STIEBEL ELTRON HPA-O 10 Premium



55 °C

35 °C



54 dB

■ 17	■ 15
■ 12	■ 11
■ 8	■ 7
kW	kW

Map of Europe with shaded regions indicating energy consumption levels.

2019

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		HPA-O 10 Premium
		238978
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Rated heating output in moderate climates for average temperature applications (Prated)	kW	12
Rated heating output in moderate climates for low temperature applications (Prated)	kW	11
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	143
Seasonal room heating efficiency in moderate climates for low temperature applications (η_s)	%	185
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	6801
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	4839
Sound power level external	dB(A)	54
Rated heating output in colder climates for average temperature applications (Prated)	kW	17
Rated heating output in colder climates for low temperature applications (Prated)	kW	15
Rated heating output in warmer climates for average temperature applications (Prated)	kW	8
Rated heating output in warmer climates for low temperature applications (Prated)	kW	7
Seasonal room heating efficiency in colder climates for average temperature applications (η_s)	%	132
Seasonal room heating efficiency in colder climates for low temperature applications (η_s)	%	165
Seasonal room heating efficiency in warmer climates for average temperature applications (η_s)	%	163
Seasonal room heating efficiency in warmer climates for low temperature applications (η_s)	%	214
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	12405
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	8804
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2581
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	1720



ENERG

енергия · ενεργεια



STIEBEL ELTRON

HPA-O 10 Premium





+ 

+ 

+ 

+ 




Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		HPA-O 10 Premium
		238978
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	143
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	147
Room heating energy efficiency of composite system under colder climatic conditions	%	136
Room heating energy efficiency of composite system under warmer climatic conditions	%	167
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	5
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	6
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		HPA-O 10 Premium
		238978
Manufacturer		STIEBEL ELTRON
Heat source		Outside air
Low temperature heat pump		-
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in colder climates for average temperature applications (Prated)	kW	17
Rated heating output in moderate climates for average temperature applications (Prated)	kW	12
Rated heating output in warmer climates for average temperature applications (Prated)	kW	8
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	10,60
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	8,40
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	7,80
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,00
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	9,90
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	9,48
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	9,48
Dual mode temperature in moderate climates (Tbiv)	°C	-5
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	132
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	143
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	163
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,69
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,51
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4,61
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		6,66
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,81
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,29
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		2,29
Heating water operating temperature limit (WTOL)	°C	65
Power consumption, OFF state (Poff)	W	10,000
Power consumption, thermostat OFF state (PTO)	W	10
Standby power consumption (PSB)	W	10,000
Power consumption, operating state, with crankcase heating (PCK)	W	38,000
Booster heater heating output (PSUB)	kW	0,690
Type of energy supply, booster heater		electric
Power control		variable
Sound power level external	dB(A)	54
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	12405
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	6801
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2581
Flow rate, heat source side	m³/h	4000