

Product datasheet: Room heater to regulation (EU) no. 811/2013

		HPA-O 13 S Premium
		238980
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Rated heating output in moderate climates for average temperature applications (Prated)	kW	15
Rated heating output in moderate climates for low temperature applications (Prated)	kW	15
Seasonal room heating efficiency in moderate climates for average temperature applications (Π s)	%	136
Seasonal room heating efficiency in moderate climates for low temperature applications (Π s)	%	173
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	8940
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	7055
Sound power level external	dB(A)	54
Rated heating output in colder climates for average temperature applications (Prated)	kW	22
Rated heating output in colder climates for low temperature applications (Prated)	kW	21
Rated heating output in warmer climates for average temperature applications (Prated)	kW	7
Rated heating output in warmer climates for low temperature applications (Prated)	kW	8
Seasonal room heating efficiency in colder climates for average temperature applications (Γ) s	%	126
Seasonal room heating efficiency in colder climates for low temperature applications $(\boldsymbol{\Pi} s)$	%	153
Seasonal room heating efficiency in warmer climates for average temperature applications (Πs)	%	155
Seasonal room heating efficiency in warmer climates for low temperature applications ($\ensuremath{\Pi} s$)	%	206
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	16814
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	13312
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2367
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	2050



ENERG Y UA ehepгия · ενεργεια IE IA

STIEBEL ELTRON

HPA-O 13 S Premium































Δ++



A

B

C

D

Ε

F

G



Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

	HPA-O 13 S Pre	mium
		238980
Manufacturer	STIEBEL EL	TRON
Seasonal room heating efficiency in moderate climates for average temperature applications (Γs)	%	136
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	140
Room heating energy efficiency of composite system under colder climatic conditions	%	130
Room heating energy efficiency of composite system under warmer climatic conditions	%	159
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	8
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	32
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		HPA-O 13 S Premium
		238980
Manufacturer		STIEBEL ELTRON
Heat source		Outside air
Low temperature heat pump		-
With booster heater		X
Combi boiler with heat pump		_
Rated heating output in colder climates for average temperature applications (Prated)	kW	22
Rated heating output in moderate climates for average temperature applications (Prated)	kW	15
Rated heating output in warmer climates for average temperature applications (Prated)	kW	7
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	13,80
$Tj=2^{\circ}C$ heating output, partial load range under moderate climatic conditions (Pdh)	kW	7,70
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	7,90
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,00
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	12,40
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	13,40
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	17,80
Dual mode temperature in moderate climates (Tbiv)	°C	-5
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	126
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	136
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	155
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,43
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,37
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4,45
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		6,66
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,53
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,28
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)	*	2,68
Operating temperature limit (Tol)	°C	-10,000
Heating water operating temperature limit (WTOL)	°C	65
Power consumption, OFF state (Poff)	W	16,000
Power consumption, thermostat OFF state (PTO)	W	16
Standby power consumption (PSB)	W	16,000
Power consumption, operating state, with crankcase heating (PCK)	W	43,000
Booster heater heating output (PSUB)	kW	0,000
Type of energy supply, booster heater		electric
Power control		variable
Sound power level external	dB(A)	54
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	16814
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	8940
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2367
Flow rate, heat source side	m³/h	4000
	*	