



ENERG Y IJA
енергия · ενέργεια IE IA

STIEBEL ELTRON HPA-O 13 CS Premium



55 °C

35 °C



A++

A+++

54 dB

22 21
15 15
7 8
kW kW

A map of Europe where different regions are shaded in various intensities of blue, corresponding to the energy consumption values listed above.

2019

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		HPA-O 13 CS Premium
		238981
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Rated heating output in moderate climates for average temperature applications (Prated)	kW	15
Rated heating output in moderate climates for low temperature applications (Prated)	kW	15
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	139
Seasonal room heating efficiency in moderate climates for low temperature applications (η_s)	%	178
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	8723
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	6839
Sound power level external	dB(A)	54
Rated heating output in colder climates for average temperature applications (Prated)	kW	22
Rated heating output in colder climates for low temperature applications (Prated)	kW	21
Rated heating output in warmer climates for average temperature applications (Prated)	kW	7
Rated heating output in warmer climates for low temperature applications (Prated)	kW	8
Seasonal room heating efficiency in colder climates for average temperature applications (η_s)	%	127
Seasonal room heating efficiency in colder climates for low temperature applications (η_s)	%	154
Seasonal room heating efficiency in warmer climates for average temperature applications (η_s)	%	174
Seasonal room heating efficiency in warmer climates for low temperature applications (η_s)	%	236
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	16684
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	13182
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2107
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	1789



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

HPA-O 13 CS Premium





+ 

+ 

+ 

+ 




Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		HPA-O 13 CS Premium
		238981
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	139
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	143
Room heating energy efficiency of composite system under colder climatic conditions	%	131
Room heating energy efficiency of composite system under warmer climatic conditions	%	178
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	8
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	32
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		HPA-O 13 CS Premium
		238981
Manufacturer		STIEBEL ELTRON
Heat source		Outside air
Low temperature heat pump		-
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in colder climates for average temperature applications (Prated)	kW	22
Rated heating output in moderate climates for average temperature applications (Prated)	kW	15
Rated heating output in warmer climates for average temperature applications (Prated)	kW	7
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	13,80
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	7,70
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	7,90
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,00
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	12,40
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	13,40
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	17,80
Dual mode temperature in moderate climates (Tbiv)	°C	-5
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	127
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	139
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	174
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,43
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,37
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4,45
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		6,66
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,53
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,28
For air/water heat pumps:Tj= -15 °C (if TOL< -20 °C) (COPd)		2,68
Operating temperature limit (Tol)	°C	-10,000
Heating water operating temperature limit (WTOL)	°C	65
Power consumption, OFF state (Poff)	W	16,000
Power consumption, thermostat OFF state (PTO)	W	16
Standby power consumption (PSB)	W	16,000
Power consumption, operating state, with crankcase heating (PCK)	W	43,000
Booster heater heating output (PSUB)	kW	0,000
Type of energy supply, booster heater		electric
Power control		variable
Sound power level external	dB(A)	54
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	16684
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	8723
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2107
Flow rate, heat source side	m³/h	4000