



**ENERG** Y IJA  
 енергия · ενέργεια IE IA

**STIEBEL ELTRON**

WPL 13 ACS classic UK  
 compact plus Set S



A+



A

57 dB



- 6 kW
- 7 kW
- 6 kW

2019

811/2013

**Product datasheet: Combi heater to regulation (EU) no. 811/2013**

		<b>WPL 13 ACS classic UK compact plus Set S</b>
		239116
Manufacturer		STIEBEL ELTRON
Load profile		L
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Energy efficiency category for DHW heating under moderate climatic conditions		A
Rated heating output in moderate climates for average temperature applications (Prated)	kW	6
Rated heating output in moderate climates for low temperature applications (Prated)	kW	7
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	4917
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	3038
Annual power consumption in moderate climates (AEC)	kWh/a	940
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	124
Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )	%	182
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under moderate climatic conditions	%	109
Sound power level external	dB(A)	57
Rated heating output in colder climates for average temperature applications (Prated)	kW	7
Rated heating output in colder climates for low temperature applications (Prated)	kW	6
Rated heating output in warmer climates for average temperature applications (Prated)	kW	7
Rated heating output in warmer climates for low temperature applications (Prated)	kW	6
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	5564
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	3675
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2128
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	1533
Annual power consumption in colder climates (AEC)	kWh/a	949
Annual power consumption in warmer climates (AEC)	kWh/a	717
Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )	%	112
Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )	%	153
Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )	%	160
Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )	%	217
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under colder climatic conditions	%	102
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under warmer climatic conditions	%	141



# ENERG

енергия · ενέργεια

Y

IJA

IE

IA

**STIEBEL ELTRON**

WPL 13 ACS classic UK compact plus Set S

Energy label for heating system components. It shows a boiler icon with an A+ rating, a radiator icon with an A+ rating, and a tap icon with an A rating.

Energy label for a radiator. It shows a radiator icon and a scale from A+++ to G. The A+++ rating is highlighted, and a black arrow points to A++.

Energy label for solar panel, hot water tank, control panel, and boiler. It shows a plus sign next to a solar panel icon, a plus sign next to a hot water tank icon, a plus sign next to a control panel icon with a hand pointing to it, and a plus sign next to a boiler icon. To the right of each icon is a square box, with the control panel box containing an 'X'.

Energy label for a tap. It shows a tap icon and a scale from A+++ to G. The A+++ rating is highlighted, and a black arrow points to A.

**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013**

		<b>WPL 13 ACS classic UK compact plus Set S</b>
		239116
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	124
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	128
Room heating energy efficiency of composite system under colder climatic conditions	%	116
Room heating energy efficiency of composite system under warmer climatic conditions	%	164
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	12
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	36
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A++
Energy efficiency category for DHW heating under moderate climatic conditions		A
Load profile		L

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		WPL 13 ACS classic UK compact plus Set S	
		239116	
Manufacturer		STIEBEL ELTRON	
Heat source		Outside air	
Low temperature heat pump			-
With booster heater			x
Combi boiler with heat pump			x
Rated heating output in colder climates for average temperature applications (Prated)	kW		7
Rated heating output in moderate climates for average temperature applications (Prated)	kW		6
Rated heating output in warmer climates for average temperature applications (Prated)	kW		7
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW		5,1
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW		4,1
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW		2,6
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW		3,3
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW		6,1
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW		5,1
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW		0
Dual mode temperature in moderate climates (Tbiv)	°C		-10
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%		112
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%		124
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%		160
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)			1,97
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)			3,18
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)			4,56
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)			5,98
Tj = dual mode temperature under moderate climatic conditions (COPd)			2,28
Tj = operating temperature limit under moderate climatic conditions (COPd)			1,97
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)			0
Operating temperature limit (Tol)	°C		-7
Heating water operating temperature limit (WTOL)	°C		60
Power consumption, OFF state (Poff)	W		17
Power consumption, thermostat OFF state (PTO)	W		30
Standby power consumption (PSB)	W		17
Power consumption, operating state, with crankcase heating (PCK)	W		5
Booster heater heating output (PSUB)	kW		7,55
Type of energy supply, booster heater			electric
Power control			variable
Sound power level external	dB(A)		57
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a		5564
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a		4917
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a		2128
Flow rate, heat source side	m <sup>3</sup> /h		2200
Load profile			L
Annual power consumption in colder climates (AEC)	kWh/a		949

Annual power consumption in moderate climates (AEC)	kWh/a	940
Annual power consumption in warmer climates (AEC)	kWh/a	717
Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions	%	109



**ENERG**  
енергия · ενέργεια



**STIEBEL ELTRON** HSBC 200 S (GB)



**55 W**

**189 L**

2017

812/2013

**Product datasheet: DHW cylinder to regulation (EU) no. 812/2013**

		<b>HSBC 200 S (GB)</b>
		236683
Manufacturer		STIEBEL ELTRON
Model identification of the supplier		HSBC 200 S (GB)
Energy efficiency class		B
Standby losses	W	55
Cylinder capacity	l	189