



ENERGY

STIEBEL ELTRON

WPL 07 ACS classic UK
compact Set S



A+



A

Two icons of a house with sound waves. The top icon is inside a rounded rectangle. Below it, the text "52 dB" is displayed.



A legend box containing three colored squares with corresponding power values: a dark blue square for "3 kW", a medium blue square for "4 kW", and a light blue square for "3 kW".

2019

811/2013

Product datasheet: Combi heater to regulation (EU) no. 811/2013

| | | WPL 07 ACS classic UK compact Set S |
|---|-------|---|
| | | 238623 |
| Manufacturer | | STIEBEL ELTRON |
| Load profile | | L |
| Energy efficiency class for central heating in moderate climates for medium temperature applications | | A+ |
| Energy efficiency class for central heating in moderate climates for low temperature applications | | A++ |
| Energy efficiency category for DHW heating under moderate climatic conditions | | A |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 3 |
| Rated heating output in moderate climates for low temperature applications (Prated) | kW | 4 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 2089 |
| Annual energy consumption in moderate climates for low temperature applications (QHE) | kWh/a | 1769 |
| Annual power consumption in moderate climates (AEC) | kWh/a | 1535 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 113 |
| Seasonal room heating efficiency in moderate climates for low temperature applications (η_s) | % | 166 |
| Energy efficiency for DHW heating (η_{wh}) under moderate climatic conditions | % | 109 |
| Sound power level external | dB(A) | 52 |
| Special measures | | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 4 |
| Rated heating output in colder climates for low temperature applications (Prated) | kW | 3 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 3 |
| Rated heating output in warmer climates for low temperature applications (Prated) | kW | 3 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 4016 |
| Annual energy consumption in colder climates for low temperature applications (QHE) | kWh/a | 2186 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 1187 |
| Annual energy consumption in warmer climates for low temperature applications (QHE) | kWh/a | 783 |
| Annual power consumption in colder climates (AEC) | kWh/a | 1663 |
| Annual power consumption in warmer climates (AEC) | kWh/a | 1253 |
| Seasonal room heating efficiency in colder climates for average temperature applications (η_s) | % | 105 |
| Seasonal room heating efficiency in colder climates for low temperature applications (η_s) | % | 150 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (η_s) | % | 139 |
| Seasonal room heating efficiency in warmer climates for low temperature applications (η_s) | % | 204 |
| Energy efficiency for DHW heating (η_{wh}) under colder climatic conditions | % | 101 |
| Energy efficiency for DHW heating (η_{wh}) under warmer climatic conditions | % | 134 |
| Operation exclusively enabled during low load times | | - |



ENERGY

STIEBEL ELTRON

WPL 07 ACS classic UK compact Set S

Icons showing a boiler, a radiator, and a tap. The boiler is labeled with an arrow pointing to 'A+' and the radiator with an arrow pointing to 'A'.

Energy efficiency scale for heating, ranging from A+++ (green) to G (red). A black arrow on the right points to the A+ level.

Icons showing a hot water tank, a control panel, and a boiler. Each icon is preceded by a plus sign and followed by a square box. The control panel box contains an 'X'.

Energy efficiency scale for hot water, ranging from A+++ (green) to G (red). A black arrow on the right points to the A level.

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

| | | WPL 07 ACS classic UK compact Set S |
|---|---|--|
| | | 238623 |
| Manufacturer | | STIEBEL ELTRON |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 113 |
| Temperature controller class | | VI |
| Contribution of temperature controller to room heating energy efficiency | % | 4 |
| Room heating energy efficiency of composite system under moderate climatic conditions | % | 117 |
| Room heating energy efficiency of composite system under colder climatic conditions | % | 109 |
| Room heating energy efficiency of composite system under warmer climatic conditions | % | 143 |
| Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions | % | 8 |
| Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions | % | 26 |
| Energy efficiency class for central heating in moderate climates for medium temperature applications | | A+ |
| Room heating energy efficiency class of composite system under moderate climatic conditions | | A+ |
| Energy efficiency category for DHW heating under moderate climatic conditions | | A |
| Load profile | | L |

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | WPL 07 ACS classic UK compact Set S | |
|---|----|-------------------------------------|------|
| | | 238623 | |
| Manufacturer | | STIEBEL ELTRON | |
| Heat source | | Outside air | |
| With booster heater | | x | |
| Combi boiler with heat pump | | - | |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | | 4 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | | 3 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | | 3 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | | 2.65 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | | 3.1 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | | 1.62 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | | 1.6 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | | 3.15 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | | 1.29 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | | 1.3 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | | 2.03 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | | 1.53 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | | 1.5 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | | 1.5 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | | 3 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | | 2.4 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | | 3.15 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | | 2.65 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | | 3.1 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | | 3.15 |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh) | kW | | 0 |
| Dual mode temperature in colder climates (Tbiv) | °C | | -10 |
| Dual mode temperature in moderate climates (Tbiv) | °C | | -5 |
| Dual mode temperature in warmer climates (Tbiv) | °C | | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs) | % | | 105 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | % | | 113 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs) | % | | 139 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | | 2.3 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | | 2.07 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | | 3.45 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | | 2.93 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | | 2.19 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | | 4.66 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | | 4.13 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | | 3.27 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | | 6.65 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | | 5.97 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | | 5.15 |
| Tj = dual mode temperature in colder climates (COPd) | | | 2.09 |
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | | 2.17 |
| Tj = dual mode temperature in warmer climates (COPd) | | | 2.19 |

| | | |
|---|---|----------|
| Tj = operating temperature limit in colder climates (COPd) | | 2.3 |
| Tj = operating temperature limit under moderate climatic conditions (COPd) | | 2.07 |
| Tj = operating temperature limit in warmer climates (COPd) | | 2.19 |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd) | | 0 |
| Heating water operating temperature limit (WTOL) | °C | 60 |
| Power consumption, OFF state (Poff) | W | 17 |
| Power consumption, thermostat OFF state (PTO) | W | 30 |
| Standby power consumption (PSB) | W | 17 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 5 |
| Booster heater heating output (PSUB) | kW | 2.93 |
| Type of energy supply, booster heater | | electric |
| Power control | | variable |
| Sound power level external | dB(A) | 52 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 4016 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 2089 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 1187 |
| Flow rate, heat source side | m ³ /h | 1300 |
| Load profile | | L |
| Annual power consumption in colder climates (AEC) | kWh/a | 1663 |
| Annual power consumption in moderate climates (AEC) | kWh/a | 1535 |
| Annual power consumption in warmer climates (AEC) | kWh/a | 1253 |
| Energy efficiency for DHW heating (Γ_{wh}) under moderate climatic conditions | % | 109 |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |