



ENERGY

STIEBEL ELTRON

WPL 07 ACS classic UK
compact plus Set S



A+



A

Two icons showing sound power level: a house with a speaker icon and a house with a speaker icon and the text '52 dB' below it.



Legend for power ratings: a dark blue square for 3 kW, a medium blue square for 4 kW, and a light blue square for 3 kW.

2019

811/2013

Product datasheet: Combi heater to regulation (EU) no. 811/2013

		WPL 07 ACS classic UK compact plus Set S
		238624
Manufacturer		STIEBEL ELTRON
Load profile		L
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Energy efficiency category for DHW heating under moderate climatic conditions		A
Rated heating output in moderate climates for average temperature applications (Prated)	kW	3
Rated heating output in moderate climates for low temperature applications (Prated)	kW	4
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	2089
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	1769
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	113
Seasonal room heating efficiency in moderate climates for low temperature applications (η_s)	%	166
Sound power level external	dB(A)	52
Special measures		For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions
Rated heating output in colder climates for average temperature applications (Prated)	kW	4
Rated heating output in colder climates for low temperature applications (Prated)	kW	3
Rated heating output in warmer climates for average temperature applications (Prated)	kW	3
Rated heating output in warmer climates for low temperature applications (Prated)	kW	3
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	4016
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	2186
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	1187
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	783
Seasonal room heating efficiency in colder climates for average temperature applications (η_s)	%	105
Seasonal room heating efficiency in colder climates for low temperature applications (η_s)	%	150
Seasonal room heating efficiency in warmer climates for average temperature applications (η_s)	%	139
Seasonal room heating efficiency in warmer climates for low temperature applications (η_s)	%	204
Operation exclusively enabled during low load times		-



ENERGY

STIEBEL ELTRON

WPL 07 ACS classic UK compact plus Set S

Icons representing energy efficiency for heating (A+) and hot water (A).

Energy efficiency scale for heating, ranging from A+++ (green) to G (red). The selected efficiency is A+.

Icons representing energy efficiency for solar (+), hot water tank (+), control (X), and boiler (+).

Energy efficiency scale for hot water, ranging from A+++ (green) to G (red). The selected efficiency is A.

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		WPL 07 ACS classic UK compact plus Set S
		238624
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	113
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	117
Room heating energy efficiency of composite system under colder climatic conditions	%	109
Room heating energy efficiency of composite system under warmer climatic conditions	%	143
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	8
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	26
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A+
Energy efficiency category for DHW heating under moderate climatic conditions		A
Load profile		L

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		WPL 07 ACS classic UK compact plus Set S	
		238624	
Manufacturer		STIEBEL ELTRON	
Heat source		Outside air	
With booster heater		x	
Combi boiler with heat pump		-	
Rated heating output in colder climates for average temperature applications (Prated)	kW	4	
Rated heating output in moderate climates for average temperature applications (Prated)	kW	3	
Rated heating output in warmer climates for average temperature applications (Prated)	kW	3	
Tj = -7 °C heating output, partial load range in colder climates (Pdh)	kW	2.65	
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	3.1	
Tj = 2 °C heating output, partial load range in colder climates (Pdh)	kW	1.62	
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	1.6	
Tj = 2 °C heating output, partial load range in warmer climates (Pdh)	kW	3.15	
Tj = 7 °C heating output, partial load range in colder climates (Pdh)	kW	1.29	
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	1.3	
Tj = 7 °C heating output, partial load range in warmer climates (Pdh)	kW	2.03	
Tj = 12 °C heating output, partial load range in colder climates (Pdh)	kW	1.53	
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	1.5	
Tj = 12 °C heating output, partial load range in warmer climates (Pdh)	kW	1.5	
Tj = dual mode temperature in colder climates (Pdh)	kW	3	
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	2.4	
Tj = dual mode temperature in warmer climates (Pdh)	kW	3.15	
Tj = operating temperature limit in colder climates (Pdh)	kW	2.65	
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	3.1	
Tj = operating temperature limit in warmer climates (Pdh)	kW	3.15	
For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	0	
Dual mode temperature in colder climates (Tbiv)	°C	-10	
Dual mode temperature in moderate climates (Tbiv)	°C	-5	
Dual mode temperature in warmer climates (Tbiv)	°C	2	
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	105	
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	113	
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	139	
Tj = -7 °C COP, partial load range in colder climates (COPd)		2.3	
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2.07	
Tj = 2 °C COP, partial load range in colder climates (COPd)		3.45	
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		2.93	
Tj = 2 °C COP, partial load range in warmer climates (COPd)		2.19	
Tj = 7 °C COP, partial load range in colder climates (COPd)		4.66	
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4.13	
Tj = 7 °C COP, partial load range in warmer climates (COPd)		3.27	
Tj = 12 °C COP, partial load range in colder climates (COPd)		6.65	
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		5.97	
Tj = 12 °C COP, partial load range in warmer climates (COPd)		5.15	
Tj = dual mode temperature in colder climates (COPd)		2.09	
Tj = dual mode temperature under moderate climatic conditions (COPd)		2.17	
Tj = dual mode temperature in warmer climates (COPd)		2.19	

Tj = operating temperature limit in colder climates (COPd)		2.3
Tj = operating temperature limit under moderate climatic conditions (COPd)		2.07
Tj = operating temperature limit in warmer climates (COPd)		2.19
For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)		0
Heating water operating temperature limit (WTOL)	°C	60
Power consumption, OFF state (Poff)	W	17
Power consumption, thermostat OFF state (PTO)	W	30
Standby power consumption (PSB)	W	17
Power consumption, operating state, with crankcase heating (PCK)	W	5
Booster heater heating output (PSUB)	kW	2.93
Type of energy supply, booster heater		electric
Power control		variable
Sound power level external	dB(A)	52
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	4016
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	2089
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	1187
Flow rate, heat source side	m ³ /h	1300
Load profile		L
Special measures	For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions	