



**ENERG**  
енергия · ενεργεια



WPL 09 IKCS classic

**STIEBEL ELTRON**



55 °C

35 °C



**A<sup>++</sup>**

**A<sup>+++</sup>**



**45** dB



**32** dB

■ 7  
■ 4  
■ 2

kW

■ 7  
■ 5  
■ 3

kW



2019

811/2013

Технические характеристики изделия:

|              |       | WPL 09 IKCS classic |
|--------------|-------|---------------------|
|              |       | 236377              |
| Manufacturer |       | STIEBEL ELTRON      |
|              |       | A++                 |
|              |       | A+++                |
|              | kW    | 4                   |
|              | kW    | 5                   |
|              | %     | 128                 |
|              | %     | 175                 |
|              | kWh/a | 2837                |
|              | kWh/a | 2178                |
|              | dB(A) | 45                  |
|              |       | -                   |
|              | kW    | 7                   |
|              | kW    | 7                   |
|              | kW    | 2                   |
|              | kW    | 3                   |
|              | %     | 116                 |
|              | %     | 150                 |
|              | %     | 136                 |
|              | %     | 198                 |
|              | kWh/a | 5547                |
|              | kWh/a | 4382                |
|              | kWh/a | 923                 |
|              | kWh/a | 698                 |
|              | dB(A) | 32                  |



# ENERG

енергия · ενεργεια



WPL 09 IKCS classic

## STIEBEL ELTRON



A<sup>++</sup>

A<sup>+++</sup>

A<sup>++</sup>

A<sup>++</sup>

A<sup>+</sup>

A

B

C

D

E

F

G

+



+



+



+



Технические характеристики изделия:

|              |   | WPL 09 IKCS classic |
|--------------|---|---------------------|
|              |   | 236377              |
| Manufacturer |   | STIEBEL ELTRON      |
|              | % | 175                 |
|              |   | VI                  |
|              | % | 4                   |
|              | % | 132                 |
|              | % | 120                 |
|              | % | 140                 |
|              | % | 12                  |
|              | % | 8                   |
|              |   | A+++                |
|              |   | A++                 |

Технические характеристики изделия:

|              |    | WPL 09 IKCS classic |
|--------------|----|---------------------|
|              |    | 236377              |
| Manufacturer |    | STIEBEL ELTRON      |
|              |    | Luft                |
|              |    | -                   |
|              |    | x                   |
|              |    | -                   |
|              | kW | 7                   |
|              | kW | 4                   |
|              | kW | 2                   |
|              | kW | 4,0                 |
|              | kW | 3,9                 |
|              | kW | 2,6                 |
|              | kW | 2,5                 |
|              | kW | 2,4                 |
|              | kW | 2,1                 |
|              | kW | 2,0                 |
|              | kW | 1,8                 |
|              | kW | 2,0                 |
|              | kW | 2,0                 |
|              | kW | 1,9                 |
|              | kW | 4,0                 |
|              | kW | 3,9                 |
|              | kW | 2,4                 |
|              | kW | 6,0                 |
|              | kW | 3,9                 |
|              | kW | 2,4                 |
|              | kW | 0,0                 |
|              | °C | -7                  |
|              | °C | -7                  |
|              | °C | 2                   |
|              | %  | 116                 |
|              | %  | 128                 |
|              | %  | 136                 |
|              |    | 2,60                |
|              |    | 2,22                |
|              |    | 3,60                |
|              |    | 3,10                |
|              |    | 2,28                |
|              |    | 5,30                |
|              |    | 4,53                |
|              |    | 3,35                |
|              |    | 7,10                |
|              |    | 6,44                |
|              |    | 5,39                |
|              |    | 2,60                |
|              |    | 2,22                |
|              |    | 2,28                |
|              |    | 1,00                |
|              |    | 2,22                |
|              |    | 2,28                |
|              |    | 0,00                |
|              | °C | 60                  |
|              | W  | 21                  |
|              | W  | 56                  |
|              | W  | 56                  |
|              | W  | 26                  |
|              | kW | 1,5                 |

|  |       |              |
|--|-------|--------------|
|  |       | elektrisch   |
|  |       | veränderlich |
|  | dB(A) | 32           |
|  | dB(A) | 45           |
|  | kWh/a | 5547         |
|  | kWh/a | 2837         |
|  | kWh/a | 923          |
|  | m³/h  | 1240         |