

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | LWZ 5 CS Premium |
|---|----|------------------|
| | | 201427 |
| Manufacturer | | STIEBEL ELTRON |
| Heat source | | Outside air |
| Low temperature heat pump | | - |
| With booster heater | | x |
| Combi boiler with heat pump | | x |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 9 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 6.00 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 7 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | 5.3 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 5.54 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | 3.3 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 3.41 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | 6.9 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | 2.8 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 2.71 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | 4.5 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | 3.2 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 3.19 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | 3.2 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | 5.3 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | 5.54 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | 6.9 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | 2.6 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | 2.67 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | 6.9 |
| Dual mode temperature in colder climates (Tbiv) | °C | -7 |
| Dual mode temperature in moderate climates (Tbiv) | °C | -7 |
| Dual mode temperature in warmer climates (Tbiv) | °C | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs) | % | 103 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | % | 129 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs) | % | 149 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | 2.52 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | 2.26 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | 3.5 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.27 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | 2.5 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | 4.56 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.09 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | 3.28 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | 5.59 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | 5.26 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | 4.98 |
| Tj = dual mode temperature in colder climates (COPd) | | 2.52 |
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | 2.26 |
| Tj = dual mode temperature in warmer climates (COPd) | | 2.5 |

| | | |
|---|---|----------|
| Tj = operating temperature limit in colder climates (COPd) | | 2.09 |
| Tj = operating temperature limit under moderate climatic conditions (COPd) | | 1.88 |
| Tj = operating temperature limit in warmer climates (COPd) | | 2.5 |
| Operating temperature limit in moderate climates (TOL) | °C | -10 |
| Heating water operating temperature limit (WTOL) | °C | 60 |
| Power consumption, OFF state (Poff) | W | 27 |
| Power consumption, thermostat OFF state (PTO) | W | 63 |
| Standby power consumption (PSB) | W | 27 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 35 |
| Booster heater heating output in moderate climate (Psup) | kW | 3.55 |
| Type of energy supply, booster heater | | electric |
| Power control | | variable |
| Sound power level external | dB(A) | 50 |
| Sound power level internal | dB(A) | 50 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 8174 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 3910 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 2420 |
| Load profile | | XL |
| Daily power consumption (Qelec) | kWh | 7.14 |
| Annual power consumption in colder climates (AEC) | kWh/a | 2042 |
| Annual power consumption in moderate climates (AEC) | kWh/a | 1676 |
| Annual power consumption in warmer climates (AEC) | kWh/a | 1183 |
| Energy efficiency for DHW heating (Γ_{wh}) under moderate climatic conditions | % | 102 |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |