

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | WPF 5 basic |
|---|----|----------------|
| | | 230944 |
| Manufacturer | | STIEBEL ELTRON |
| Heat source | | Brine |
| With booster heater | | x |
| Combi boiler with heat pump | | - |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 7 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 5 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 5 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | 5.6 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 5.40 |
| Tj = -7 °C heating output, partial load range in warmer climates (Pdh) | kW | 5.3 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | 5.7 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 5.60 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | 5.3 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | 5.8 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 5.70 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | 5.5 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | 5.9 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 5.80 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | 5.7 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | 5.5 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | 5.30 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | 5.3 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | 5.3 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | 5.30 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | 5.3 |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh) | kW | 5.30 |
| Dual mode temperature in colder climates (Tbiv) | °C | -15 |
| Dual mode temperature in moderate climates (Tbiv) | °C | -10 |
| Dual mode temperature in warmer climates (Tbiv) | °C | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs) | % | 123 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | % | 118 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs) | % | 116 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | 3.07 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | 2.58 |
| Tj = -7 °C COP, partial load range in warmer climates (COPd) | | 2.45 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | 3.48 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.08 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | 2.45 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | 3.87 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.48 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | 2.84 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | 4.21 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.97 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | 3.64 |
| Tj = dual mode temperature in colder climates (COPd) | | 2.85 |

| | | |
|---|---|----------|
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | 2.45 |
| Tj = dual mode temperature in warmer climates (COPd) | | 2.45 |
| Tj = operating temperature limit in colder climates (COPd) | | 2.45 |
| Tj = operating temperature limit under moderate climatic conditions (COPd) | | 2.45 |
| Tj = operating temperature limit in warmer climates (COPd) | | 2.45 |
| For air/water heat pumps: Tj= -15 °C (if TOL < -20 °C) (COPd) | | 2.45 |
| Heating water operating temperature limit (WTOL) | °C | 60 |
| Power consumption, OFF state (Poff) | W | 0.000 |
| Power consumption, thermostat OFF state (PTO) | W | 78 |
| Standby power consumption (PSB) | W | 3.000 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 0.000 |
| Booster heater heating output in moderate climate (Psup) | kW | 0.000 |
| Type of energy supply, booster heater | | electric |
| Power control | | Fixed |
| Sound power level internal | dB(A) | 46 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 5045 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 3489 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 2283 |
| Flow rate, heat source side | m ³ /h | 1,4 |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |