## Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014

Manufacturer  Model identification of the supplier  Specific energy consumption in colder climates, central demand- dependent control  Specific energy consumption in average climates, central demand- dependent control  Specific energy consumption in warmer climates, central demand- dependent control  kWh/(m² p.a.)  kWh/(m² p.a.)	000047
Model identification of the supplier  Specific energy consumption in colder climates, central demand- dependent control  Specific energy consumption in average climates, central demand- dependent control  Specific energy consumption in warmer climates, central demand- dependent control  kWh/(m² p.a.)  kWh/(m² p.a.)	236647
Specific energy consumption in colder climates, central demand- dependent control  Specific energy consumption in average climates, central demand- dependent control  Specific energy consumption in warmer climates, central demand- dependent control  kWh/(m² p.a.)  kWh/(m² p.a.)	STIEBEL ELTRON
dependent control  Specific energy consumption in average climates, central demand- dependent control  Specific energy consumption in warmer climates, central demand- dependent control  kWh/(m² p.a.)  kWh/(m² p.a.)	LWZ 280 Enthalpie
dependent control  Specific energy consumption in warmer climates, central demand- dependent control  kWh/(m² p.a.)	-72.98
dependent control	-37.73
	-14.91
Energy efficiency class in colder climates, central demand-dependent control	A+
Energy efficiency class in average climates, central demand-dependent control	A
Energy efficiency class in warmer climates, central demand-dependent control	Е
Ventilation unit type	Two directions
Drive type	Variable speed
Heat recovery method	Recovery
Rate of temperature change for heat recovery %	75.9
Max. air flow rate m³/h	350
Max. power consumption W	105
Sound power level Lwa dB(A)	47.7
Reference air flow rate m³/s	0.068
Reference pressure differential Pa	50
Specific input W/(m³/h)	0.19
Control factor, central demand-dependent control	0,85
Declared maximum internal leakage rates %	1,14
Declared maximum external leakage rates %	0.32
Filter change indicator  Visual filter chan	ge indicator integrated in display of the remote control
Internet address for assembly and disassembly instructions	www.stiebel-eltron.com
Annual power consumption in colder climates with central demand-dependent control kWh/a	781
Annual power consumption in average climates with central demand-dependent control kWh/a	244
Annual power consumption in warmer climates with central demand-dependent control kWh/a	199
Annual heating savings in colder climates with central demand-dependent control kWh/a	8310
Annual heating savings in average climates with central demand-dependent control kWh/a	4248
Annual heating savings in warmer climates with central demand-dependent control kWh/a	1921