

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | WPE-I 12 HW 230 Premium |
|---|----|--------------------------------|
| | | 202478 |
| Manufacturer | | STIEBEL ELTRON |
| Heat source | | Brine |
| Low temperature heat pump | | - |
| With booster heater | | x |
| Combi boiler with heat pump | | x |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 12 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 12 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 12 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | 7.24 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 10.59 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | 4.4 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 6.44 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | 11.99 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | 2.82 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 4.13 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | 7.69 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | 2.23 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 2.21 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | 3.41 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | 11.99 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | 11.99 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | 11.99 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | 11.99 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | 11.99 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | 11.99 |
| Dual mode temperature in colder climates (Tbiv) | °C | -22 |
| Dual mode temperature in moderate climates (Tbiv) | °C | -10 |
| Dual mode temperature in warmer climates (Tbiv) | °C | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs) | % | 174.3 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | % | 169 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs) | % | 167.6 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | 4.31 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.55 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | 4.91 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.49 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | 3.29 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | 5.16 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.99 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | 4.12 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | 5.4 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | 5.25 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | 5.1 |
| Tj = dual mode temperature in colder climates (COPd) | | 3.29 |
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | 3.29 |
| Tj = dual mode temperature in warmer climates (COPd) | | 3.29 |

| | | |
|---|---|----------|
| Tj = operating temperature limit in colder climates (COPd) | | 3.29 |
| Tj = operating temperature limit under moderate climatic conditions (COPd) | | 3.29 |
| Tj = operating temperature limit in warmer climates (COPd) | | 3.29 |
| Operating temperature limit in moderate climates (TOL) | °C | -10 |
| Heating water operating temperature limit (WTOL) | °C | 75 |
| Power consumption, OFF state (Poff) | W | 19 |
| Power consumption, thermostat OFF state (PTO) | W | 19 |
| Standby power consumption (PSB) | W | 19 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 0 |
| Booster heater heating output in colder climates (Psup) | kW | 0 |
| Booster heater heating output in moderate climate (Psup) | kW | 0.00 |
| Booster heater heating output in warmer climates (Psup) | kW | 0 |
| Type of energy supply, booster heater | | electric |
| Power control | | variable |
| Sound power level internal | dB(A) | 44 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 6485 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 5607 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 3650 |
| Flow rate, heat source side | m³/h | 1,08 |
| Load profile | | XL |
| Daily power consumption in colder climates (QELEC) | kWh | 6.61 |
| Daily power consumption (Qelec) | kWh | 6.61 |
| Daily power consumption in warmer climates (QELEC) | kWh | 6.61 |
| Annual power consumption in colder climates (AEC) | kWh/a | 1451 |
| Annual power consumption in moderate climates (AEC) | kWh/a | 1451 |
| Annual power consumption in warmer climates (AEC) | kWh/a | 1451 |
| Energy efficiency for DHW heating (η_{wh}) under moderate climatic conditions | % | 115 |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |