Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014

| Model identification of the supplier Specific energy consumption in colder climates, time control Specific energy consumption in average climates, time control KWh/(m² p.a.) -78.34 Specific energy consumption in warmer climates, time control kWh/(m² p.a.) -15.32 Energy efficiency class in colder climates, time control Energy efficiency class in average climates, time control Energy efficiency class in warmer climates, time control Energy efficiency efficiency class in warmer climates, time control Energy efficiency effic | | | LWZ 180 Balance Set 1 |
|---|--|-----------------------|---|
| Model identification of the supplier Specific energy consumption in colder climates, time control KWh/(m² p.a.) \$\text{2.80}\$. \$\text{3.83}\$ Specific energy consumption in average climates, time control KWh/(m² p.a.) \$\text{3.99.95}\$ \$\text{3.99.95}\$ \$\text{3.99.15}\$ \$\tex | | | 236881 |
| Specific energy consumption in colder climates, time control Specific energy consumption in average climates, time control Specific energy consumption in average climates, time control Specific energy consumption in warmer climates, time control Specific energy consumption in warmer climates, time control Specific energy costs in colder climates, time control Specific energy class in colder climates, time control Atheracy efficiency class in average climates, time control Atheracy efficiency class in average climates, time control Atheracy efficiency class in warmer climates, time control Atheracy efficiency efficiency class in warmer climates, time control Atheracy efficiency effic | Manufacturer | | STIEBEL ELTRON |
| Specific energy consumption in average climates, time control kWh/(m² p.a.) -39.95 Specific energy consumption in warmer climates, time control kWh/(m² p.a.) -15.32 Energy efficiency class in colder climates, time control A Energy efficiency class in average climates, time control E Ventilation unit type WLA, Two directions Drive type WLA, Two directions Ventilation unit type Variable speed Heat recovery method Recovery Rate of temperature change for heat recovery % 89.3 Max. air flow rate m³/h 250 Max. power consumption W 74 Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control 0.95 Declared maximum internal leakage rates % 0.04 Filter change indicator Optical filter change indicator in the remote control di | Model identification of the supplier | | LWZ 180 balance set 1 |
| Specific energy consumption in warmer climates, time control kWh/(m² p.a.) -15.32 Energy efficiency class in colder climates, time control A+ Energy efficiency class in average climates, time control A Energy efficiency class in average climates, time control E Ventilation unit type WLA, Two directions Drive type Variable speed Heat recovery method Recovery Rate of temperature change for heat recovery % 89.3 Max. air flow rate m³/h 250 Max. power consumption W 74 Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control W/(m³/h) 0.19 Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly i | Specific energy consumption in colder climates, time control | kWh/(m² p.a.) | -78.34 |
| Energy efficiency class in colder climates, time control Energy efficiency class in average climates, time control Energy efficiency class in average climates, time control Eventilation unit type WLA, Two directions Drive type WLA, Two directions Drive type Variable speed Heat recovery method Recovery Rate of temperature change for heat recovery Rate of temperature change for heat re | Specific energy consumption in average climates, time control | kWh/(m² p.a.) | -39.95 |
| Energy efficiency class in average climates, time control Energy efficiency class in warmer climates, time control Energy efficiency class in warmer climates, time control Eventilation unit type Wariable speed Recovery Rate of temperature change for heat recovery Rate of temperature change for heat recovery Rate of temperature change for heat recovery Max. air flow rate Max. power consumption Wax. power consumption Wax. power level Lwa Beference air flow rate May a Reference air flow rate Reference air flow rate May a Specific input Control factor, time control Declared maximum internal leakage rates Wax. population of the system Filter change indicator Filter change indicator Internet address for assembly and disassembly instructions Annual power consumption in colder climates with time control Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumption in warmer climates with time control KWh/a Annual power consumptio | Specific energy consumption in warmer climates, time control | kWh/(m² p.a.) | -15.32 |
| Energy efficiency class in warmer climates, time control Ventilation unit type Variable speed Recovery Rate of temperature change for heat recovery Rate of temperature change in flow rate Rate of the speak of the | Energy efficiency class in colder climates, time control | | A+ |
| Ventilation unit type WLA, Two directions Drive type Variable speed Heat recovery method Recovery Rate of temperature change for heat recovery % 89.3 Max. air flow rate m³/h 250 Max. power consumption W 74 Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control 0.95 0.63 Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % 0.04361 Filter change indicator Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in varrage climates with time control kWh/a 260 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 457 | Energy efficiency class in average climates, time control | | A |
| Drive type Variable speed Heat recovery method Recovery Rate of temperature change for heat recovery % 89.3 Max. air flow rate m³/h 250 Max. power consumption W 74 Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Specific input W/(m³/h) 0.01 Control factor, time control 0.95 0.63 Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % 0.044 Filter change indicator Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in average climates with time control | Energy efficiency class in warmer climates, time control | | E |
| Heat recovery method Recovery Rate of temperature change for heat recovery % 89.3 Max. air flow rate m³/h 250 Max. power consumption W 74 Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference air flow rate m³/s 0.04861 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control W/(m³/h) 0.19 Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % 0.044 Filter change indicator Pilter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions Internet address for assembly and disassembly instructions Www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Ventilation unit type | | WLA, Two directions |
| Rate of temperature change for heat recovery % 88.3 Max. air flow rate m³/h 250 Max. power consumption W 74 Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control W/(m³/h) 0.19 Control factor, time control 0,95 0.63 Declared maximum internal leakage rates % 0,63 0.63 Declared maximum external leakage rates % Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a www.stiebel-eltron.com Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 2853 Annual heating savings in colder climates with time control kWh/a | Drive type | | Variable speed |
| Max. air flow rate m³/h 250 Max. power consumption W 74 Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control 0,95 Declared maximum internal leakage rates % 0,63 Declared maximum external leakage rates % Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Heat recovery method | | Recovery |
| Max. power consumption W 74 Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control W/(m³/h) 0.19 Declared maximum internal leakage rates 9% 0.63 Declared maximum external leakage rates 9% 0.044 Filter change indicator Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions Wh/a 797 Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Rate of temperature change for heat recovery | % | 89.3 |
| Sound power level Lwa dB(A) 43 Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control 0.95 Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % 0.63 Declared maximum external leakage rates % 0.644 Filter change indicator control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Max. air flow rate | m³/h | 250 |
| Reference air flow rate m³/s 0.04861 Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control 0.95 Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % Optical filter change indicator in the remote Filter change indicator Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 3953 Annual heating savings in colder climates with time control kWh/a 4577 | Max. power consumption | W | 74 |
| Reference pressure differential Pa 50 Specific input W/(m³/h) 0.19 Control factor, time control 0,95 Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in warmer climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 3215 Annual heating savings in colder climates with time control kWh/a 4577 | Sound power level Lwa | dB(A) | 43 |
| Specific input W/(m³/h) 0.19 Control factor, time control 0,95 Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % 0.44 Filter change indicator Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Reference air flow rate | m³/s | 0.04861 |
| Control factor, time control Declared maximum internal leakage rates Declared maximum external leakage rates Moptical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions Annual power consumption in colder climates with time control Annual power consumption in average climates with time control Annual power consumption in warmer climates with time control Annual power consumption in variage climates with time control Annual heating savings in colder climates with time control KWh/a Annual heating savings in average climates with time control KWh/a Annual heating savings in average climates with time control KWh/a Annual heating savings in average climates with time control KWh/a | Reference pressure differential | Pa | 50 |
| Declared maximum internal leakage rates % 0.63 Declared maximum external leakage rates % Optical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 4573 Annual heating savings in average climates with time control kWh/a 4577 | Specific input | W/(m ³ /h) | 0.19 |
| Declared maximum external leakage rates Moptical filter change indicator in the remote control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions Annual power consumption in colder climates with time control Annual power consumption in average climates with time control Annual power consumption in warmer climates with time control Annual power consumption in warmer climates with time control Annual heating savings in colder climates with time control Annual heating savings in average climates with time control KWh/a Annual heating savings in average climates with time control KWh/a 4577 | Control factor, time control | | 0,95 |
| Filter change indicator Filter change indicator Filter change indicator Control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions Annual power consumption in colder climates with time control Annual power consumption in average climates with time control Annual power consumption in warmer climates with time control Annual power consumption in warmer climates with time control Annual heating savings in colder climates with time control KWh/a Annual heating savings in average climates with time control KWh/a Annual heating savings in average climates with time control KWh/a Annual heating savings in average climates with time control KWh/a | Declared maximum internal leakage rates | % | 0.63 |
| Filter change indicator control display Attention: A regular filter change is important for a low energy efficiency of the system. Internet address for assembly and disassembly instructions www.stiebel-eltron.com Annual power consumption in colder climates with time control kWh/a Annual power consumption in average climates with time control kWh/a Annual power consumption in warmer climates with time control kWh/a Annual heating savings in colder climates with time control kWh/a Annual heating savings in average climates with time control kWh/a Annual heating savings in average climates with time control kWh/a Annual heating savings in average climates with time control kWh/a | Declared maximum external leakage rates | % | 0.44 |
| Annual power consumption in colder climates with time control kWh/a 797 Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Filter change indicator | | control display Attention: A regular filter change is |
| Annual power consumption in average climates with time control kWh/a 260 Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Internet address for assembly and disassembly instructions | | www.stiebel-eltron.com |
| Annual power consumption in warmer climates with time control kWh/a 215 Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Annual power consumption in colder climates with time control | kWh/a | 797 |
| Annual heating savings in colder climates with time control kWh/a 8953 Annual heating savings in average climates with time control kWh/a 4577 | Annual power consumption in average climates with time control | kWh/a | 260 |
| Annual heating savings in average climates with time control kWh/a 4577 | Annual power consumption in warmer climates with time control | kWh/a | 215 |
| | Annual heating savings in colder climates with time control | kWh/a | 8953 |
| Annual heating savings in warmer climates with time control kWh/a 2069 | Annual heating savings in average climates with time control | kWh/a | 4577 |
| | Annual heating savings in warmer climates with time control | kWh/a | 2069 |