



**ENERG** Y IJA  
 енергия · ενέργεια IE IA

**STIEBEL ELTRON**

WPE-I 15 HKW 230  
 Premium



**A+++**



**A**

45 dB



- 14 kW
- 14 kW
- 14 kW

2019

811/2013

**Product datasheet: Combi heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

|   |   | <b>WPE-I 15 HKW 230 Premium</b> |
|---|---|---------------------------------|
|   |   | 202481                          |
| Manufacturer  |   | STIEBEL ELTRON                  |
| Load profile  |   | XL                              |
| Energy efficiency class for central heating in moderate climates for medium temperature applications    |   | A+++                            |
| Energy efficiency class for central heating in moderate climates for low temperature applications       |   | A+++                            |
| Energy efficiency category for DHW heating under moderate climatic conditions                           |   | A                               |
| Rated heating output in moderate climates for average temperature applications (Prated)                 | kW  | 14                              |
| Rated heating output in moderate climates for low temperature applications (Prated)                     | kW  | 14                              |
| Annual energy consumption in moderate climates for average temperature applications (QHE)               | kWh/a   | 6476                            |
| Annual energy consumption in moderate climates for low temperature applications (QHE)                   | kWh/a   | 5489                            |
| Annual power consumption in moderate climates (AEC)   | kWh/a   | 1451                            |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ ) | %   | 168                             |
| Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )     | %   | 210                             |
| Energy efficiency for DHW heating ( $\eta_{wh}$ ) under moderate climatic conditions                    | %   | 115                             |
| Sound power level internal  | dB(A)   | 45                              |
| Special measures  | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |                                 |
| Rated heating output in colder climates for average temperature applications (Prated)                   | kW  | 14                              |
| Rated heating output in colder climates for low temperature applications (Prated)                       | kW  | 14                              |
| Rated heating output in warmer climates for average temperature applications (Prated)                   | kW  | 14                              |
| Rated heating output in warmer climates for low temperature applications (Prated)                       | kW  | 14                              |
| Annual energy consumption in colder climates for average temperature applications (QHE)                 | kWh/a   | 7451                            |
| Annual energy consumption in colder climates for low temperature applications (QHE)                     | kWh/a   | 6298                            |
| Annual energy consumption in warmer climates for average temperature applications (QHE)                 | kWh/a   | 4211                            |
| Annual energy consumption in warmer climates for low temperature applications (QHE)                     | kWh/a   | 3573                            |
| Annual power consumption in colder climates (AEC)   | kWh/a   | 1451                            |
| Annual power consumption in warmer climates (AEC)   | kWh/a   | 1451                            |
| Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )   | %   | 174.2                           |
| Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )       | %   | 218.4                           |
| Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )   | %   | 166.7                           |
| Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )       | %   | 208.3                           |
| Energy efficiency for DHW heating ( $\eta_{wh}$ ) under colder climatic conditions                      | %   | 115                             |
| Energy efficiency for DHW heating ( $\eta_{wh}$ ) under warmer climatic conditions                      | %   | 115                             |
| Operation exclusively enabled during low load times   |   | -                               |



# ENERG

енергия · ενέργεια



**STIEBEL ELTRON**

WPE-I 15 HKW 230 Premium





















**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

|   |   | <b>WPE-I 15 HKW 230 Premium</b> |
|---|---|---------------------------------|
|   |   | 202481                          |
| Manufacturer  |   | STIEBEL ELTRON                  |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )                                   | % | 168                             |
| Contribution of temperature controller to room heating energy efficiency  | % | 4                               |
| Room heating energy efficiency of composite system under moderate climatic conditions   | % | 177.7                           |
| Room heating energy efficiency of composite system under colder climatic conditions   | % | 177.7                           |
| Room heating energy efficiency of composite system under warmer climatic conditions   | % | 170.2                           |
| Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions | % | 6.5                             |
| Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions | % | 1                               |
| Energy efficiency class for central heating in moderate climates for medium temperature applications                                      |   | A+++                            |
| Room heating energy efficiency class of composite system under moderate climatic conditions   |   | A+++                            |
| Energy efficiency category for DHW heating under moderate climatic conditions   |   | A                               |
| Load profile  |   | XL                              |

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

|   |    | WPE-I 15 HKW 230 Premium |
|---|----|--------------------------|
|   |    | 202481                   |
| Manufacturer  |    | STIEBEL ELTRON           |
| Heat source   |    | Brine                    |
| Low temperature heat pump   |    | -                        |
| With booster heater   |    | x                        |
| Combi boiler with heat pump   |    | x                        |
| Rated heating output in colder climates for average temperature applications (Prated)           | kW | 14                       |
| Rated heating output in moderate climates for average temperature applications (Prated)         | kW | 14                       |
| Rated heating output in warmer climates for average temperature applications (Prated)           | kW | 14                       |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh)                          | kW | 8.32                     |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 12.16                    |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh)                           | kW | 5.05                     |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 7.4                      |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 13.77                    |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh)                           | kW | 3.24                     |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 4.75                     |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 8.83                     |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh)                          | kW | 2.23                     |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 2.22                     |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh)                          | kW | 3.92                     |
| Tj = dual mode temperature in colder climates (Pdh)   | kW | 13.77                    |
| Tj = dual mode temperature under moderate climatic conditions (Pdh)                             | kW | 13.77                    |
| Tj = dual mode temperature in warmer climates (Pdh)   | kW | 13.77                    |
| Tj = operating temperature limit in colder climates (Pdh)                                       | kW | 13.77                    |
| Tj = operating temperature limit under moderate climatic conditions (Pdh)                       | kW | 13.77                    |
| Tj = operating temperature limit in warmer climates (Pdh)                                       | kW | 13.77                    |
| Dual mode temperature in colder climates (Tbiv)   | °C | -22                      |
| Dual mode temperature in moderate climates (Tbiv)   | °C | -10                      |
| Dual mode temperature in warmer climates (Tbiv)   | °C | 2                        |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs)   | %  | 174.2                    |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | %  | 168                      |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)   | %  | 166.7                    |
| Tj = -7 °C COP, partial load range in colder climates (COPd)                                    |    | 4.24                     |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 3.4                      |
| Tj = 2 °C COP, partial load range in colder climates (COPd)                                     |    | 4.94                     |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 4.44                     |
| Tj = 2 °C COP, partial load range in warmer climates (COPd)                                     |    | 3.26                     |
| Tj = 7 °C COP, partial load range in colder climates (COPd)                                     |    | 5.24                     |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 5.03                     |
| Tj = 7 °C COP, partial load range in warmer climates (COPd)                                     |    | 3.99                     |
| Tj = 12 °C COP, partial load range in colder climates (COPd)                                    |    | 5.44                     |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 5.31                     |
| Tj = 12 °C COP, partial load range in warmer climates (COPd)                                    |    | 5.16                     |
| Tj = dual mode temperature in colder climates (COPd)  |    | 3.26                     |
| Tj = dual mode temperature under moderate climatic conditions (COPd)                            |    | 3.26                     |
| Tj = dual mode temperature in warmer climates (COPd)  |    | 3.26                     |

|   |   |          |
|---|---|----------|
| Tj = operating temperature limit in colder climates (COPd)                                |   | 3.26     |
| Tj = operating temperature limit under moderate climatic conditions (COPd)                |   | 3.26     |
| Tj = operating temperature limit in warmer climates (COPd)                                |   | 3.26     |
| Operating temperature limit in moderate climates (TOL)                                    | °C  | -10.000  |
| Heating water operating temperature limit (WTOL)  | °C  | 75       |
| Power consumption, OFF state (Poff)   | W   | 19.000   |
| Power consumption, thermostat OFF state (PTO)   | W   | 19       |
| Standby power consumption (PSB)   | W   | 19.000   |
| Power consumption, operating state, with crankcase heating (PCK)                          | W   | 0.000    |
| Booster heater heating output in colder climates (Psup)                                   | kW  | 0        |
| Booster heater heating output (PSUB)  | kW  | 0        |
| Booster heater heating output in warmer climates (Psup)                                   | kW  | 0        |
| Type of energy supply, booster heater   |   | electric |
| Power control   |   | variable |
| Sound power level internal  | dB(A)   | 45       |
| Annual energy consumption in colder climates for average temperature applications (QHE)   | kWh/a   | 7451     |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a   | 6476     |
| Annual energy consumption in warmer climates for average temperature applications (QHE)   | kWh/a   | 4211     |
| Flow rate, heat source side   | m <sup>3</sup> /h   | 1,31     |
| Load profile  |   | XL       |
| Daily power consumption in colder climates (QELEC)  | kWh   | 6.61     |
| Daily power consumption (Qelec)   | kWh   | 6.61     |
| Daily power consumption in warmer climates (QELEC)  | kWh   | 6.61     |
| Annual power consumption in colder climates (AEC)   | kWh/a   | 1451     |
| Annual power consumption in moderate climates (AEC)                                       | kWh/a   | 1451     |
| Annual power consumption in warmer climates (AEC)   | kWh/a   | 1451     |
| Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions    | %   | 115      |
| Special measures  | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |          |