



ENERG Y IJA
 енергия · ενέργεια IE IA

STIEBEL ELTRON WPF 10 S basic



55 °C

35 °C



A+

A+++


51 dB



■ 11	■ 12
■ 9	■ 10
■ 9	■ 10
kW	kW



2019

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)

		WPF 10 S basic
		220819
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Rated heating output in moderate climates for average temperature applications (Prated)	kW	9
Rated heating output in moderate climates for low temperature applications (Prated)	kW	10
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	118
Seasonal room heating efficiency in moderate climates for low temperature applications (η_s)	%	196
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	5743
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	4018
Sound power level internal	dB(A)	51
Special measures		For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions
Rated heating output in colder climates for average temperature applications (Prated)	kW	11
Rated heating output in colder climates for low temperature applications (Prated)	kW	12
Rated heating output in warmer climates for average temperature applications (Prated)	kW	9
Rated heating output in warmer climates for low temperature applications (Prated)	kW	10
Seasonal room heating efficiency in colder climates for average temperature applications (η_s)	%	124
Seasonal room heating efficiency in colder climates for low temperature applications (η_s)	%	205
Seasonal room heating efficiency in warmer climates for average temperature applications (η_s)	%	117
Seasonal room heating efficiency in warmer climates for low temperature applications (η_s)	%	195
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	8318
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	5719
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	3733
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	2606



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

WPF 10 S basic





+ 

+ 

+ 

+ 



A+++

A++

A+ 

A

B

C

D

E

F

G

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)

		WPF 10 S basic
		220819
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications (η_s)	%	118
Temperature controller class		VII
Contribution of temperature controller to room heating energy efficiency	%	3
Room heating energy efficiency of composite system under moderate climatic conditions	%	122
Room heating energy efficiency of composite system under colder climatic conditions	%	128
Room heating energy efficiency of composite system under warmer climatic conditions	%	121
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	6
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	1
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A+

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		WPF 10 S basic
		220819
Manufacturer		STIEBEL ELTRON
Heat source		Brine
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in colder climates for average temperature applications (Prated)	kW	11
Rated heating output in moderate climates for average temperature applications (Prated)	kW	9
Rated heating output in warmer climates for average temperature applications (Prated)	kW	9
Tj = -7 °C heating output, partial load range in colder climates (Pdh)	kW	9.3
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	8.9
Tj = -7 °C heating output, partial load range in warmer climates (Pdh)	kW	8.8
Tj = 2 °C heating output, partial load range in colder climates (Pdh)	kW	9.5
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9.3
Tj = 2 °C heating output, partial load range in warmer climates (Pdh)	kW	8.8
Tj = 7 °C heating output, partial load range in colder climates (Pdh)	kW	9.7
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9.5
Tj = 7 °C heating output, partial load range in warmer climates (Pdh)	kW	9.1
Tj = 12 °C heating output, partial load range in colder climates (Pdh)	kW	9.8
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9.7
Tj = 12 °C heating output, partial load range in warmer climates (Pdh)	kW	9.6
Tj = dual mode temperature in colder climates (Pdh)	kW	9.1
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	8.8
Tj = dual mode temperature in warmer climates (Pdh)	kW	8.8
Tj = operating temperature limit in colder climates (Pdh)	kW	8.8
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	8.8
Tj = operating temperature limit in warmer climates (Pdh)	kW	8.8
For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	8.8
Dual mode temperature in colder climates (Tbiv)	°C	-15
Dual mode temperature in moderate climates (Tbiv)	°C	-10
Dual mode temperature in warmer climates (Tbiv)	°C	2
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	124
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	118
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	117
Tj = -7 °C COP, partial load range in colder climates (COPd)		3.07
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2.53
Tj = -7 °C COP, partial load range in warmer climates (COPd)		2.40
Tj = 2 °C COP, partial load range in colder climates (COPd)		3.52
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3.08
Tj = 2 °C COP, partial load range in warmer climates (COPd)		2.40
Tj = 7 °C COP, partial load range in colder climates (COPd)		3.96
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		3.52
Tj = 7 °C COP, partial load range in warmer climates (COPd)		2.82
Tj = 12 °C COP, partial load range in colder climates (COPd)		4.34
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		4.07
Tj = 12 °C COP, partial load range in warmer climates (COPd)		3.69
Tj = dual mode temperature in colder climates (COPd)		2.84

Tj = dual mode temperature under moderate climatic conditions (COPd)		2.40
Tj = dual mode temperature in warmer climates (COPd)		2.40
Tj = operating temperature limit in colder climates (COPd)		2.40
Tj = operating temperature limit under moderate climatic conditions (COPd)		2.40
Tj = operating temperature limit in warmer climates (COPd)		2.40
For air/water heat pumps: Tj= -15 °C (if TOL < -20 °C) (COPd)		2.40
Heating water operating temperature limit (WTOL)	°C	60
Power consumption, OFF state (Poff)	W	0.000
Power consumption, thermostat OFF state (PTO)	W	95
Standby power consumption (PSB)	W	5
Power consumption, operating state, with crankcase heating (PCK)	W	0
Booster heater heating output in moderate climate (Psup)	kW	0.0
Type of energy supply, booster heater		electric
Power control		Fixed
Sound power level internal	dB(A)	51
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	8318
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	5743
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	3733
Flow rate, heat source side	m ³ /h	2,2
Special measures	For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions	