



ENERG
енергия · ενέργεια

Y IJA
IE IA

STIEBEL ELTRON WPL 25 A



55 °C

35 °C



A++

A++

54 dB

■ 22	■ 21
■ 15	■ 15
■ 8	■ 8
kW	kW

2015

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		WPL 25 A
		232493
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Rated heating output in moderate climates for medium temperature applications	kW	15
Rated heating output in moderate climates for low temperature applications	kW	15
Energy efficiency for central heating in moderate climates for medium temperature applications	%	141
Energy efficiency for central heating in moderate climates for low temperature applications	%	183
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	8858
Energy consumption for central heating under moderate climatic conditions, for low temperature applications	kWh/a	6491
Rated heating output in colder climates for medium temperature applications	kW	22
Rated heating output in colder climates for low temperature applications	kW	21
Rated heating output in warmer climates for medium temperature applications	kW	8
Rated heating output in warmer climates for low temperature applications	kW	8
Energy efficiency for central heating in colder climates for medium temperature applications	%	132
Energy efficiency for central heating in colder climates for low temperature applications	%	162
Energy efficiency for central heating in warmer climates for medium temperature applications	%	165
Energy efficiency for central heating in warmer climates for low temperature applications	%	220
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	16172
Energy consumption for central heating under colder climatic conditions, for low temperature applications	kWh/a	12287
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	2678
Energy consumption for central heating under warmer climatic conditions, for low temperature applications	kWh/a	1997
Sound power level external	dB(A)	54



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

WPL 25 A



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C


D

E

F

G

+



+



+



+



Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

			WPL 25 A
			232493
Manufacturer			STIEBEL ELTRON
Energy efficiency for central heating in moderate climates for medium temperature applications		%	141
Temperature controller class			VI
Contribution of temperature controller to room heating energy efficiency		%	4
Room heating energy efficiency of composite system under moderate climatic conditions		%	145
Room heating energy efficiency of composite system under colder climatic conditions		%	136
Room heating energy efficiency of composite system under warmer climatic conditions		%	169
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions		%	9
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions		%	24
Energy efficiency class for central heating in moderate climates for medium temperature applications			A++
Room heating energy efficiency class of composite system under moderate climatic conditions			A++

Product datasheet: Temperature controller to regulation (EU) no. 811/2013

		WPL 25 A
		232493
Manufacturer		STIEBEL ELTRON
Heat source		Outside air
{Niedertemperatur-Wärmepumpe}		-
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in moderate climates for medium temperature applications	kW	15
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	12,8
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	8,3
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	8,0
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	7,0
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	11,8
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	14,4
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	17,0
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,98
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		4,72
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		6,16
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		8,10
Tj = dual mode temperature under moderate climatic conditions (COPd)		3,16
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,79
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		2,58
Dual mode temperature (Tbiv)	°C	-5
Heating water operating temperature limit (WTOL)	°C	65
Power consumption, OFF state (Poff)	W	10
Power consumption, thermostat OFF state (PTO)	W	10
Standby power consumption (PSB)	W	10
Power consumption, operating state, with crankcase heating (PCK)	W	38
Booster heater heating output (PSUB)	kW	0,21
Type of energy supply, booster heater		electric
Power control		variable
Sound power level external	dB(A)	54
Flow rate, heat source side	m ³ /h	4000