



ENERG Y IJA
 енергия · ενέργεια IE IA

STIEBEL ELTRON WPC 10 cool



A++



A

48 dB



- 13 kW
- 10 kW
- 10 kW

2015

811/2013

		WPC 10 cool
		232934
Manufacturer		STIEBEL ELTRON
Load profile		XL
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Energy efficiency category for DHW heating under moderate climatic conditions		A
Rated heating output in moderate climates for medium temperature applications	kW	9
Rated heating output in moderate climates for low temperature applications	kW	10
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	5176
Energy consumption for central heating under moderate climatic conditions, for low temperature applications	kWh/a	3799
Energy consumption for DHW heating under moderate climatic conditions	kWh/a	1529
Energy efficiency for central heating in moderate climates for medium temperature applications	%	137
Energy efficiency for central heating in moderate climates for low temperature applications	%	216
Energy efficiency for DHW heating (η_{wh}) under moderate climatic conditions	%	110
Sound power level internal	dB(A)	48
{Spezielle Vorsichtsmaßnahmen}		Alle spezifischen Vorkehrungen bei Montage, Installation und Wartung sind in der Bedienungs- und Installationsanleitung beschrieben.
Rated heating output in colder climates for medium temperature applications	kW	12
Rated heating output in colder climates for low temperature applications	kW	13
Rated heating output in warmer climates for medium temperature applications	kW	9
Rated heating output in warmer climates for low temperature applications	kW	10
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	7549
Energy consumption for central heating under colder climatic conditions, for low temperature applications	kWh/a	5457
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	3367
Energy consumption for central heating under warmer climatic conditions, for low temperature applications	kWh/a	2466
Energy consumption for DHW heating under colder climatic conditions	kWh/a	1529
Energy consumption for DHW heating under warmer climatic conditions	kWh/a	1529
Energy efficiency for central heating in colder climates for medium temperature applications	%	144
Energy efficiency for central heating in colder climates for low temperature applications	%	224
Energy efficiency for central heating in warmer climates for medium temperature applications	%	136
Energy efficiency for central heating in warmer climates for low temperature applications	%	215
Energy efficiency for DHW heating (η_{wh}) under colder climatic conditions	%	110
Energy efficiency for DHW heating (η_{wh}) under warmer climatic conditions	%	110



ENERG

енергия · ενέργεια



STIEBEL ELTRON

WPC 10 cool

A++

A

XL

A+++

A++

A+

A

B

C

D

E

F

G

A++

+

+

+

+

X

XL

A+++

A++

A+

A

B

C

D

E

F

G

A

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

			WPC 10 cool
			232934
Manufacturer			STIEBEL ELTRON
Energy efficiency for central heating in moderate climates for medium temperature applications		%	137
Temperature controller class			VII
Contribution of temperature controller to room heating energy efficiency		%	3,5
Room heating energy efficiency of composite system under moderate climatic conditions		%	140,5
Room heating energy efficiency of composite system under colder climatic conditions		%	147,5
Room heating energy efficiency of composite system under warmer climatic conditions		%	139,5
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions		%	7
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions		%	1
Energy efficiency class for central heating in moderate climates for medium temperature applications			A++
Room heating energy efficiency class of composite system under moderate climatic conditions			A++
Energy efficiency category for DHW heating under moderate climatic conditions			A
Load profile			XL

		WPC 10 cool
		232934
Manufacturer		STIEBEL ELTRON
Heat source		Brine
Low temperature heat pump		-
With booster heater		x
Combi boiler with heat pump		x
Rated heating output in moderate climates for medium temperature applications	kW	9
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,2
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,6
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,9
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	10,1
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	9,1
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	9,1
For air/water heat pumps:Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	9,1
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,97
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,56
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4,03
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		4,6
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,83
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,83
For air/water heat pumps:Tj = -15 °C (if TOL < -20 °C) (COPd)		2,83
Dual mode temperature (Tbiv)	°C	-10
Operating temperature limit (Tol)	°C	-10
Heating water operating temperature limit (WTOL)	°C	65
Power consumption, OFF state (Poff)	W	0
Power consumption, thermostat OFF state (PTO)	W	84
Standby power consumption (PSB)	W	9
Power consumption, operating state, with crankcase heating (PCK)	W	0
Booster heater heating output (PSUB)	kW	0
Type of energy supply, booster heater		electric
Power control		Fixed
Sound power level internal	dB(A)	48
Flow rate, heat source side	m ³ /h	2,61
Load profile		XL
Energy efficiency for DHW heating (η _{wh}) under moderate climatic conditions	%	110
Daily power consumption (Q _{elec})	kWh	7,01