



ENERG
енергия · ενέργεια

Y IJA
IE IA

STIEBEL ELTRON WPW 13 Set



55 °C

35 °C



A++

A++



■ 14
■ 9
■ 5
kW

■ 15
■ 10
■ 6
kW



2015

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		WPW 13 Set
		232951
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Rated heating output in moderate climates for medium temperature applications	kW	9
Rated heating output in moderate climates for low temperature applications	kW	10
Energy efficiency for central heating in moderate climates for medium temperature applications	%	137
Energy efficiency for central heating in moderate climates for low temperature applications	%	216
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	5191
Energy consumption for central heating under moderate climatic conditions, for low temperature applications	kWh/a	3814
Rated heating output in colder climates for medium temperature applications	kW	14
Rated heating output in colder climates for low temperature applications	kW	15
Rated heating output in warmer climates for medium temperature applications	kW	5
Rated heating output in warmer climates for low temperature applications	kW	6
Energy efficiency for central heating in colder climates for medium temperature applications	%	141
Energy efficiency for central heating in colder climates for low temperature applications	%	213
Energy efficiency for central heating in warmer climates for medium temperature applications	%	128
Energy efficiency for central heating in warmer climates for low temperature applications	%	202
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	9327
Energy consumption for central heating under colder climatic conditions, for low temperature applications	kWh/a	6903
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	1992
Energy consumption for central heating under warmer climatic conditions, for low temperature applications	kWh/a	1473



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

WPW 13 Set



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺

A

B

C

D

E

F

G

+		<input type="checkbox"/>
+		<input type="checkbox"/>
+		<input checked="" type="checkbox"/>
+		<input type="checkbox"/>

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		WPW 13 Set
		232951
Manufacturer		STIEBEL ELTRON
Energy efficiency for central heating in moderate climates for medium temperature applications	%	137
Temperature controller class		VII
Contribution of temperature controller to room heating energy efficiency	%	3,5
Room heating energy efficiency of composite system under moderate climatic conditions	%	220
Room heating energy efficiency of composite system under colder climatic conditions	%	213
Room heating energy efficiency of composite system under warmer climatic conditions	%	202
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	7
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	17
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++



ENERG
енергия · ενέργεια

Y IJA
IE IA

STIEBEL ELTRON WPF 10



55 °C

35 °C



A++

A++

48 dB

■ 12	■ 13
■ 9	■ 10
■ 9	■ 10

kW kW

2015

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		WPF 10
		232912
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Rated heating output in moderate climates for medium temperature applications	kW	9
Rated heating output in moderate climates for low temperature applications	kW	10
Energy efficiency for central heating in moderate climates for medium temperature applications	%	137
Energy efficiency for central heating in moderate climates for low temperature applications	%	216
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	5176
Energy consumption for central heating under moderate climatic conditions, for low temperature applications	kWh/a	3799
Sound power level internal	dB(A)	48
Rated heating output in colder climates for medium temperature applications	kW	12
Rated heating output in colder climates for low temperature applications	kW	13
Rated heating output in warmer climates for medium temperature applications	kW	9
Rated heating output in warmer climates for low temperature applications	kW	10
Energy efficiency for central heating in colder climates for medium temperature applications	%	144
Energy efficiency for central heating in colder climates for low temperature applications	%	224
Energy efficiency for central heating in warmer climates for medium temperature applications	%	136
Energy efficiency for central heating in warmer climates for low temperature applications	%	215
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	7549
Energy consumption for central heating under colder climatic conditions, for low temperature applications	kWh/a	5457
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	3367
Energy consumption for central heating under warmer climatic conditions, for low temperature applications	kWh/a	2466



ENERG

енергия · ενεργεια

Y

IJA



IE





IA




STIEBEL ELTRON

WPF 10









+ 
 + 
 + 
 + 



Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		WPF 10
		232912
Manufacturer		STIEBEL ELTRON
Energy efficiency for central heating in moderate climates for medium temperature applications	%	137
Temperature controller class		VII
Contribution of temperature controller to room heating energy efficiency	%	3,5
Room heating energy efficiency of composite system under moderate climatic conditions	%	141
Room heating energy efficiency of composite system under colder climatic conditions	%	148
Room heating energy efficiency of composite system under warmer climatic conditions	%	140
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	7
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	1
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Product datasheet: Temperature controller to regulation (EU) no. 811/2013

		WPF 10
		232912
Manufacturer		STIEBEL ELTRON
Heat source		Brine
{Niedertemperatur-Wärmepumpe}		-
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in moderate climates for medium temperature applications	kW	9
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,2
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,6
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,9
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	10,1
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	9,1
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	9,1
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	9,1
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,97
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,56
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4,03
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		4,60
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,83
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,83
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		2,83
Dual mode temperature (Tbiv)	°C	-10
Heating water operating temperature limit (WTOL)	°C	65
Power consumption, OFF state (Poff)	W	0
Power consumption, thermostat OFF state (PTO)	W	84
Standby power consumption (PSB)	W	9
Power consumption, operating state, with crankcase heating (PCK)	W	0
Booster heater heating output (PSUB)	kW	0,00
Type of energy supply, booster heater		electric
Power control		Fixed
Sound power level internal	dB(A)	48
Flow rate, heat source side	m ³ /h	2,61