



**ENERG** Y IJA  
 енергия · ενέργεια IE IA

**STIEBEL ELTRON** WPC 10 S GB



**A++**



**A**

49 dB



- 12 kW
- 9 kW
- 9 kW

2019

811/2013

**Product datasheet: Combi heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

|   |       | <b>WPC 10 S GB</b>  |
|---|-------|---|
|   |       | 234310  |
| Manufacturer  |       | STIEBEL ELTRON  |
| Load profile  |       | XL  |
| Energy efficiency class for central heating in moderate climates for medium temperature applications    |       | A++   |
| Energy efficiency class for central heating in moderate climates for low temperature applications       |       | A+++  |
| Energy efficiency category for DHW heating under moderate climatic conditions                           |       | A   |
| Rated heating output in moderate climates for average temperature applications (Prated)                 | kW    | 9   |
| Rated heating output in moderate climates for low temperature applications (Prated)                     | kW    | 10  |
| Annual energy consumption in moderate climates for average temperature applications (QHE)               | kWh/a | 5358  |
| Annual energy consumption in moderate climates for low temperature applications (QHE)                   | kWh/a | 4091  |
| Annual power consumption in moderate climates (AEC)   | kWh/a | 1529  |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ ) | %     | 136   |
| Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )     | %     | 200   |
| Energy efficiency for DHW heating ( $\eta_{wh}$ ) under moderate climatic conditions                    | %     | 110   |
| Sound power level internal  | dB(A) | 49  |
| Special measures  |       | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |
| Rated heating output in colder climates for average temperature applications (Prated)                   | kW    | 12  |
| Rated heating output in colder climates for low temperature applications (Prated)                       | kW    | 13  |
| Rated heating output in warmer climates for average temperature applications (Prated)                   | kW    | 9   |
| Rated heating output in warmer climates for low temperature applications (Prated)                       | kW    | 10  |
| Annual energy consumption in colder climates for average temperature applications (QHE)                 | kWh/a | 7799  |
| Annual energy consumption in colder climates for low temperature applications (QHE)                     | kWh/a | 5895  |
| Annual energy consumption in warmer climates for average temperature applications (QHE)                 | kWh/a | 3488  |
| Annual energy consumption in warmer climates for low temperature applications (QHE)                     | kWh/a | 2660  |
| Annual power consumption in colder climates (AEC)   | kWh/a | 1529  |
| Annual power consumption in warmer climates (AEC)   | kWh/a | 1529  |
| Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )   | %     | 141   |
| Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )       | %     | 206   |
| Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )   | %     | 135   |
| Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )       | %     | 199   |
| Energy efficiency for DHW heating ( $\eta_{wh}$ ) under colder climatic conditions                      | %     | 110   |
| Energy efficiency for DHW heating ( $\eta_{wh}$ ) under warmer climatic conditions                      | %     | 110   |
| Operation exclusively enabled during low load times   |       | -   |



# ENERG

енергия · ενέργεια

Y

IJA

IE

IA

**STIEBEL ELTRON**

WPC 10 S GB

A++

A

A+++

A++

A+

A

B

C

D

E

F

G

A++

+

+

+

+

X

XL

A+++

A++

A+

A

B

C

D

E

F

G

A

**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

|   |   | <b>WPC 10 S GB</b> |
|---|---|--------------------|
|   |   | 234310             |
| Manufacturer  |   | STIEBEL ELTRON     |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )                                   | % | 136                |
| Temperature controller class  |   | VII                |
| Contribution of temperature controller to room heating energy efficiency  | % | 3.50               |
| Room heating energy efficiency of composite system under moderate climatic conditions   | % | 140                |
| Room heating energy efficiency of composite system under colder climatic conditions   | % | 145                |
| Room heating energy efficiency of composite system under warmer climatic conditions   | % | 139                |
| Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions | % | 5                  |
| Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions | % | 1                  |
| Energy efficiency class for central heating in moderate climates for medium temperature applications                                      |   | A++                |
| Room heating energy efficiency class of composite system under moderate climatic conditions   |   | A++                |
| Energy efficiency category for DHW heating under moderate climatic conditions   |   | A                  |
| Load profile  |   | XL                 |

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

|   |    | WPC 10 S GB    |
|---|----|----------------|
|   |    | 234310         |
| Manufacturer  |    | STIEBEL ELTRON |
| Heat source   |    | Brine          |
| With booster heater   |    | x              |
| Combi boiler with heat pump   |    | x              |
| Rated heating output in colder climates for average temperature applications (Prated)           | kW | 12             |
| Rated heating output in moderate climates for average temperature applications (Prated)         | kW | 9              |
| Rated heating output in warmer climates for average temperature applications (Prated)           | kW | 9              |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh)                          | kW | 9.8            |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 9.50           |
| Tj = -7 °C heating output, partial load range in warmer climates (Pdh)                          | kW | 9.4            |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh)                           | kW | 10             |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 9.80           |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 9.4            |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh)                           | kW | 10.2           |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 10.00          |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 9.6            |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh)                          | kW | 10.3           |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 10.20          |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh)                          | kW | 10.1           |
| Tj = dual mode temperature in colder climates (Pdh)   | kW | 9.6            |
| Tj = dual mode temperature under moderate climatic conditions (Pdh)                             | kW | 9.40           |
| Tj = dual mode temperature in warmer climates (Pdh)   | kW | 9.4            |
| Tj = operating temperature limit in colder climates (Pdh)                                       | kW | 9.6            |
| Tj = operating temperature limit under moderate climatic conditions (Pdh)                       | kW | 9.40           |
| Tj = operating temperature limit in warmer climates (Pdh)                                       | kW | 9.4            |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)                                   | kW | 9.40           |
| Dual mode temperature in colder climates (Tbiv)   | °C | -15            |
| Dual mode temperature in moderate climates (Tbiv)   | °C | -10            |
| Dual mode temperature in warmer climates (Tbiv)   | °C | 2              |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs)   | %  | 141            |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | %  | 136            |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)   | %  | 135            |
| Tj = -7 °C COP, partial load range in colder climates (COPd)                                    |    | 3.53           |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 3.03           |
| Tj = -7 °C COP, partial load range in warmer climates (COPd)                                    |    | 2.9            |
| Tj = 2 °C COP, partial load range in colder climates (COPd)                                     |    | 3.95           |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 3.55           |
| Tj = 2 °C COP, partial load range in warmer climates (COPd)                                     |    | 2.9            |
| Tj = 7 °C COP, partial load range in colder climates (COPd)                                     |    | 4.33           |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 3.95           |
| Tj = 7 °C COP, partial load range in warmer climates (COPd)                                     |    | 3.3            |
| Tj = 12 °C COP, partial load range in colder climates (COPd)                                    |    | 4.65           |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 4.43           |
| Tj = 12 °C COP, partial load range in warmer climates (COPd)                                    |    | 4.1            |
| Tj = dual mode temperature in colder climates (COPd)  |    | 3.31           |

|   |   |          |
|---|---|----------|
| Tj = dual mode temperature under moderate climatic conditions (COPd)                      |   | 2.90     |
| Tj = dual mode temperature in warmer climates (COPd)                                      |   | 2.9      |
| Tj = operating temperature limit in colder climates (COPd)                                |   | 2.9      |
| Tj = operating temperature limit under moderate climatic conditions (COPd)                |   | 2.90     |
| Tj = operating temperature limit in warmer climates (COPd)                                |   | 2.9      |
| For air/water heat pumps: Tj= -15 °C (if TOL < -20 °C) (COPd)                             |   | 2.90     |
| Heating water operating temperature limit (WTOL)  | °C  | 60       |
| Power consumption, OFF state (Poff)   | W   | 0        |
| Power consumption, thermostat OFF state (PTO)   | W   | 85       |
| Standby power consumption (PSB)   | W   | 10       |
| Power consumption, operating state, with crankcase heating (PCK)                          | W   | 0        |
| Booster heater heating output in moderate climate (Psup)                                  | kW  | 0.00     |
| Type of energy supply, booster heater   |   | electric |
| Power control   |   | Fixed    |
| Sound power level internal  | dB(A)   | 49       |
| Annual energy consumption in colder climates for average temperature applications (QHE)   | kWh/a   | 7799     |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a   | 5358     |
| Annual energy consumption in warmer climates for average temperature applications (QHE)   | kWh/a   | 3488     |
| Flow rate, heat source side   | m <sup>3</sup> /h   | 2,54     |
| Load profile  |   | XL       |
| Daily power consumption in colder climates (QELEC)  | kWh   | 7.01     |
| Daily power consumption (Qelec)   | kWh   | 7.01     |
| Daily power consumption in warmer climates (QELEC)  | kWh   | 7.01     |
| Annual power consumption in colder climates (AEC)   | kWh/a   | 1529     |
| Annual power consumption in moderate climates (AEC)                                       | kWh/a   | 1529     |
| Annual power consumption in warmer climates (AEC)   | kWh/a   | 1529     |
| Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions    | %   | 110      |
| Special measures  | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |          |