



# ENERGY

**STIEBEL ELTRON**

WPE-I 10 HW 400 Plus



**A++**



**A**

**42 dB**



- 11 kW
- 11 kW
- 12 kW

2019

811/2013

**Product datasheet: Combi heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

|                                                                                                         |       | <b>WPE-I 10 HW 400 Plus</b> |
|---------------------------------------------------------------------------------------------------------|-------|-----------------------------|
|                                                                                                         |       | 205836                      |
| Manufacturer                                                                                            |       | STIEBEL ELTRON              |
| Load profile                                                                                            |       | XL                          |
| Energy efficiency class for central heating in moderate climates for medium temperature applications    |       | A++                         |
| Energy efficiency class for central heating in moderate climates for low temperature applications       |       | A+++                        |
| Energy efficiency category for DHW heating under moderate climatic conditions                           |       | A                           |
| Rated heating output in moderate climates for average temperature applications (Prated)                 | kW    | 12                          |
| Rated heating output in moderate climates for low temperature applications (Prated)                     | kW    | 11                          |
| Annual energy consumption in moderate climates for average temperature applications (QHE)               | kWh/a | 6357                        |
| Annual energy consumption in moderate climates for low temperature applications (QHE)                   | kWh/a | 4327                        |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ ) | %     | 145                         |
| Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )     | %     | 195                         |
| Energy efficiency for DHW heating ( $\eta_{wh}$ ) under moderate climatic conditions                    | %     | 104                         |
| Sound power level internal                                                                              | dB(A) | 42                          |
| Rated heating output in colder climates for average temperature applications (Prated)                   | kW    | 11                          |
| Rated heating output in colder climates for low temperature applications (Prated)                       | kW    | 11                          |
| Rated heating output in warmer climates for average temperature applications (Prated)                   | kW    | 11                          |
| Rated heating output in warmer climates for low temperature applications (Prated)                       | kW    | 12                          |
| Annual energy consumption in colder climates for average temperature applications (QHE)                 | kWh/a | 7085                        |
| Annual energy consumption in colder climates for low temperature applications (QHE)                     | kWh/a | 5400                        |
| Annual energy consumption in warmer climates for average temperature applications (QHE)                 | kWh/a | 3818                        |
| Annual energy consumption in warmer climates for low temperature applications (QHE)                     | kWh/a | 3009                        |
| Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )   | %     | 150                         |
| Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )       | %     | 202                         |
| Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )   | %     | 147                         |
| Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )       | %     | 198                         |



# ENERGY

**STIEBEL ELTRON**

WPE-I 10 HW 400 Plus

Icons representing energy efficiency for heating and hot water. The heating icon is labeled **A++** and the hot water icon is labeled **A**.

Energy efficiency scale for heating, showing a range from **A+++** (green) to **G** (red). The selected efficiency level is **A++**.

Icons representing energy efficiency for solar, hot water tank, control, and boiler. The solar icon is labeled **+**, the hot water tank icon is labeled **+**, the control icon is labeled **X**, and the boiler icon is labeled **+**.

Energy efficiency scale for hot water, showing a range from **A+++** (green) to **G** (red). The selected efficiency level is **A**.

**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

|                                                                                                         |   | <b>WPE-I 10 HW 400 Plus</b> |
|---------------------------------------------------------------------------------------------------------|---|-----------------------------|
|                                                                                                         |   | 205836                      |
| Manufacturer                                                                                            |   | STIEBEL ELTRON              |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ ) | % | 145                         |
| Temperature controller class                                                                            |   | III                         |
| Room heating energy efficiency of composite system under moderate climatic conditions                   | % | 147                         |
| Room heating energy efficiency of composite system under colder climatic conditions                     | % | 151                         |
| Room heating energy efficiency of composite system under warmer climatic conditions                     | % | 148                         |
| Energy efficiency class for central heating in moderate climates for medium temperature applications    |   | A++                         |
| Room heating energy efficiency class of composite system under moderate climatic conditions             |   | A++                         |
| Energy efficiency category for DHW heating under moderate climatic conditions                           |   | A                           |
| Load profile                                                                                            |   | XL                          |

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

|                                                                                                         |    | <b>WPE-I 10 HW 400 Plus</b> |
|---------------------------------------------------------------------------------------------------------|----|-----------------------------|
|                                                                                                         |    | 205836                      |
| Manufacturer                                                                                            |    | STIEBEL ELTRON              |
| Low temperature heat pump                                                                               |    | -                           |
| Combi boiler with heat pump                                                                             |    | x                           |
| Rated heating output in colder climates for average temperature applications (Prated)                   | kW | 11                          |
| Rated heating output in moderate climates for average temperature applications (Prated)                 | kW | 12                          |
| Rated heating output in warmer climates for average temperature applications (Prated)                   | kW | 11                          |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh)                                  | kW | 9.6                         |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)                  | kW | 9.4                         |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh)                                   | kW | 9.7                         |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)                   | kW | 9.6                         |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh)                                   | kW | 9.2                         |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh)                                   | kW | 9.8                         |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)                   | kW | 9.8                         |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh)                                   | kW | 9.5                         |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh)                                  | kW | 9.9                         |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)                  | kW | 9.9                         |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh)                                  | kW | 9.8                         |
| Tj = dual mode temperature in colder climates (Pdh)                                                     | kW | 9.5                         |
| Tj = dual mode temperature under moderate climatic conditions (Pdh)                                     | kW | 9.5                         |
| Tj = dual mode temperature in warmer climates (Pdh)                                                     | kW | 9.4                         |
| Tj = operating temperature limit in colder climates (Pdh)                                               | kW | 9.2                         |
| Tj = operating temperature limit under moderate climatic conditions (Pdh)                               | kW | 9.2                         |
| Tj = operating temperature limit in warmer climates (Pdh)                                               | kW | 9.2                         |
| Dual mode temperature in colder climates (Tbiv)                                                         | °C | -16                         |
| Dual mode temperature in moderate climates (Tbiv)                                                       | °C | -5                          |
| Dual mode temperature in warmer climates (Tbiv)                                                         | °C | 4                           |
| Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )   | %  | 150                         |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ ) | %  | 145                         |
| Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )   | %  | 147                         |
| Tj = -7 °C COP, partial load range in colder climates (COPd)                                            |    | 3.72                        |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)                            |    | 3.26                        |
| Tj = 2 °C COP, partial load range in colder climates (COPd)                                             |    | 4.15                        |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)                             |    | 3.86                        |
| Tj = 2 °C COP, partial load range in warmer climates (COPd)                                             |    | 3.02                        |
| Tj = 7 °C COP, partial load range in colder climates (COPd)                                             |    | 4.54                        |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)                             |    | 4.24                        |
| Tj = 7 °C COP, partial load range in warmer climates (COPd)                                             |    | 3.57                        |
| Tj = 12 °C COP, partial load range in colder climates (COPd)                                            |    | 4.87                        |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)                            |    | 4.69                        |
| Tj = 12 °C COP, partial load range in warmer climates (COPd)                                            |    | 4.37                        |
| Tj = dual mode temperature in colder climates (COPd)                                                    |    | 3.44                        |
| Tj = dual mode temperature under moderate climatic conditions (COPd)                                    |    | 3.44                        |
| Tj = dual mode temperature in warmer climates (COPd)                                                    |    | 3.31                        |
| Tj = operating temperature limit in colder climates (COPd)                                              |    | 3.02                        |

|                                                                                           |                   |          |
|-------------------------------------------------------------------------------------------|-------------------|----------|
| Tj = operating temperature limit under moderate climatic conditions (COPd)                |                   | 3.02     |
| Tj = operating temperature limit in warmer climates (COPd)                                |                   | 3.02     |
| Heating water operating temperature limit (WTOL)                                          | °C                | 65       |
| Power consumption, OFF state (Poff)                                                       | W                 | 4        |
| Power consumption, thermostat OFF state (PTO)                                             | W                 | 8        |
| Standby power consumption (PSB)                                                           | W                 | 8        |
| Power consumption, operating state, with crankcase heating (PCK)                          | W                 | 0        |
| Booster heater heating output in colder climates (Psup)                                   | kW                | 2.1      |
| Booster heater heating output in moderate climate (Psup)                                  | kW                | 2.5      |
| Booster heater heating output in warmer climates (Psup)                                   | kW                | 1.8      |
| Type of energy supply, booster heater                                                     |                   | electric |
| Sound power level internal                                                                | dB(A)             | 42       |
| Annual energy consumption in colder climates for average temperature applications (QHE)   | kWh/a             | 7085     |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a             | 6357     |
| Annual energy consumption in warmer climates for average temperature applications (QHE)   | kWh/a             | 3818     |
| Flow rate, heat source side                                                               | m <sup>3</sup> /h | 1,8      |
| Load profile                                                                              |                   | XL       |
| Daily power consumption in colder climates (QELEC)                                        | kWh               | 7.525    |
| Daily power consumption (Qelec)                                                           | kWh               | 7.525    |
| Daily power consumption in warmer climates (QELEC)                                        | kWh               | 7.525    |
| Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions    | %                 | 104      |