




ENERGY



WPL-I 10.2 Plus HK 400

STIEBEL ELTRON



55 °C

35 °C



- dB



- dB



kW



kW

2019

811/2013

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)



		WPL-I 10.2 Plus HK 400
		210121
Manufacturer		STIEBEL ELTRON
Space heating energy efficiency class under average climate conditions, medium-temperature applications (A+++ -> D)		-
Energy efficiency class, space heating under average climate conditions, low-temperature applications (A+++ -> D)		-
Rated heating output under average climate conditions for medium-temperature applications (P rated)		-
Rated heating output under average climate conditions for low-temperature applications (P rated)		-
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)		-
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)		-
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)		-
Annual energy consumption under average climate conditions for low-temperature applications (QHE)		-
Sound power level, indoor		-
Option for operation only at off-peak times		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)		-
Rated heating output under colder climate conditions for low-temperature applications (P rated)		-
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)		-
Rated heating output under warmer climate conditions for low-temperature applications (P rated)		-
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)		-
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s)		-
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)		-
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)		-
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)		-
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)		-
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)		-
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)		-
Sound power level, outdoor		-



ENERGY

WPL-I 10.2 Plus HK 400

STIEBEL ELTRON



A⁺⁺⁺

A⁺⁺

A⁺

A

B


C

D


E

F

G



+



+



+



+



Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		WPL-I 10.2 Plus HK 400
		210121
Manufacturer		STIEBEL ELTRON
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)		-
Temperature control class		-
Contribution of temperature control to space heating energy efficiency		-
Space heating energy efficiency of package under average climate conditions		-
Space heating energy efficiency of package under colder climate conditions		-
Space heating energy efficiency of package under warmer climate conditions		-
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions		-
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions		-
Energy efficiency class, space heating under average climate conditions, low-temperature applications (A+++ -> D)		-
Space heating energy efficiency class of package under average climate conditions (A+++ -> D)		-

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		WPL-I 10.2 Plus HK 400
		210121
Manufacturer		STIEBEL ELTRON
Heat source		-
Low temperature heat pump		-
With auxiliary heater		-
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)		-
Rated heating output under average climate conditions for medium-temperature applications (P rated)		-
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)		-
T _j = -7 °C heating output, partial load range under colder climate conditions (P _{dh})		-
T _j = -7 °C heating output, partial load range under average climate conditions (P _{dh})		-
T _j = 2 °C heating output, partial load range under colder climate conditions (P _{dh})		-
T _j = 2 °C heating output, partial load range under average climate conditions (P _{dh})		-
T _j = 2 °C heating output, partial load range under warmer climate conditions (P _{dh})		-
T _j = 7 °C heating output, partial load range under colder climate conditions (P _{dh})		-
T _j = 7 °C heating output, partial load range under average climate conditions (P _{dh})		-
T _j = 7 °C heating output, partial load range under warmer climate conditions (P _{dh})		-
T _j = 12 °C heating output, partial load range under colder climate conditions (P _{dh})		-
T _j = 12 °C heating output, partial load range under average climate conditions (P _{dh})		-
T _j = 12 °C heating output, partial load range under warmer climate conditions (P _{dh})		-
T _j = dual mode temperature under colder climate conditions (P _{dh})		-
T _j = dual mode temperature under average climate conditions (P _{dh})		-
T _j = dual mode temperature under warmer climate conditions (P _{dh})		-
T _j = operating temperature limit under colder climate conditions (P _{dh})		-
T _j = operating temperature limit under average climate conditions (P _{dh})		-
T _j = operating temperature limit under warmer climate conditions (P _{dh})		-
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (P _{dh})		-
Dual mode temperature under colder climate conditions (T _{biv})		-
Dual mode temperature under average climate conditions (T _{biv})		-
Dual mode temperature under warmer climate conditions (T _{biv})		-
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η _s)		-
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η _s)		-
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η _s)		-
T _j = -7 °C COP, partial load range under colder climate conditions (COP _d)		-
T _j = -7 °C COP, partial load range under average climate conditions (COP _d)		-
T _j = 2 °C COP, partial load range under colder climate conditions (COP _d)		-
T _j = 2 °C COP, partial load range under average climate conditions (COP _d)		-
T _j = 2 °C COP, partial load range under warmer climate conditions (COP _d)		-
T _j = 7 °C COP, partial load range under colder climate conditions (COP _d)		-
T _j = 7 °C COP, partial load range under average climate conditions (COP _d)		-

Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		-
Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		-
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		-
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		-
Tj = dual mode temperature under colder climate conditions (COPd)		-
Tj = dual mode temperature under average climate conditions (COPd)		-
Tj = dual mode temperature under warmer climate conditions (COPd)		-
Tj = operating temperature limit under colder climate conditions (COPd)		-
Tj = operating temperature limit under average climate conditions (COPd)		-
Tj = operating temperature limit under warmer climate conditions (COPd)		-
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)		-
Operating temperature limit under colder climate conditions (TOL)		-
Operating temperature limit under average climate conditions (TOL)		-
Operating temperature limit under warmer climate conditions (TOL)		-
Operating temperature limit of heating water under colder climate conditions (WTOL)		-
Operating temperature limit of heating water under average climate conditions (WTOL)		-
Operating temperature limit of heating water under warmer climate conditions (WTOL)		-
Power consumption, off-mode (Poff)		-
Power consumption, thermostat off-mode (PTO)		-
Power consumption, standby state (PSB)		-
Power consumption, operating state, with crankcase heating (PCK)		-
Rated heating output of auxiliary heater under colder climate conditions (PSUP)		-
Rated heating output of auxiliary heater under average climate conditions (PSUP)		-
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)		-
Type of energy supply, auxiliary heater		-
Output control		-
Sound power level, outdoor		-
Sound power level, indoor		-
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)		-
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)		-
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)		-
Flow rate on heat source side		-