




# ENERGY

**STIEBEL ELTRON**

LWZ 130 Enthalpie  
manual



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**


|  |                           | <b>LWZ 130 Enthalpie</b>   |
|--|---------------------------|--|
|  |                           | 237806   |
| Manufacturer   |                           | STIEBEL ELTRON   |
| Model identification of the supplier                             |                           | LWZ 130 Enthalpie  |
| Specific energy consumption in colder climates, manual control   | kWh/(m <sup>2</sup> p.a.) | -67.38   |
| Specific energy consumption in average climates, manual control  | kWh/(m <sup>2</sup> p.a.) | -32.84   |
| Specific energy consumption in warmer climates, manual control   | kWh/(m <sup>2</sup> p.a.) | -10.42   |
| Energy efficiency class in colder climates, manual control       |                           | A+   |
| Energy efficiency class in average climates, manual control      |                           | B  |
| Energy efficiency class in warmer climates, manual control       |                           | E  |
| Ventilation unit type  |                           | Two directions   |
| Drive type   |                           | Variable speed   |
| Heat recovery method   |                           | Recovery   |
| Rate of temperature change for heat recovery                     | %                         | 77.2   |
| Max. air flow rate   | m <sup>3</sup> /h         | 180  |
| Max. power consumption   | W                         | 105  |
| Sound power level Lwa  | dB(A)                     | 33   |
| Reference air flow rate  | m <sup>3</sup> /s         | 0.035  |
| Reference pressure differential                                  | Pa                        | 50   |
| Specific input   | W/(m <sup>3</sup> /h)     | 0.27   |
| Control factor, manual control                                   |                           | 1  |
| Declared maximum internal leakage rates                          | %                         | 2,22   |
| Declared maximum external leakage rates                          | %                         | 2.78   |
| Filter change indicator  |                           | Visual filter change indicator integrated in display of the remote control |
| Internet address for assembly and disassembly instructions       |                           | <a href="http://www.stiebel-eltron.com">www.stiebel-eltron.com</a>         |
| Annual power consumption in colder climates with manual control  | kWh/a                     | 920  |
| Annual power consumption in average climates with manual control | kWh/a                     | 383  |
| Annual power consumption in warmer climates with manual control  | kWh/a                     | 338  |
| Annual heating savings in colder climates with manual control    | kWh/a                     | 8166   |
| Annual heating savings in average climates with manual control   | kWh/a                     | 4174   |
| Annual heating savings in warmer climates with manual control    | kWh/a                     | 1888   |



# ENERGY

**STIEBEL ELTRON**

LWZ 130 Enthalpie  
clock



**33**  
dB

**180 m<sup>3</sup>/h**

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**

|  |                           | <b>LWZ 130 Enthalpie</b>   |
|--|---------------------------|--|
|  |                           | 237806   |
| Manufacturer   |                           | STIEBEL ELTRON   |
| Model identification of the supplier                           |                           | LWZ 130 Enthalpie  |
| Specific energy consumption in colder climates, time control   | kWh/(m <sup>2</sup> p.a.) | -68.92   |
| Specific energy consumption in average climates, time control  | kWh/(m <sup>2</sup> p.a.) | -34.02   |
| Specific energy consumption in warmer climates, time control   | kWh/(m <sup>2</sup> p.a.) | -11.41   |
| Energy efficiency class in colder climates, time control       |                           | A+   |
| Energy efficiency class in average climates, time control      |                           | A  |
| Energy efficiency class in warmer climates, time control       |                           | E  |
| Ventilation unit type  |                           | Two directions   |
| Drive type   |                           | Variable speed   |
| Heat recovery method   |                           | Recovery   |
| Rate of temperature change for heat recovery                   | %                         | 77.2   |
| Max. air flow rate   | m <sup>3</sup> /h         | 180  |
| Max. power consumption   | W                         | 105  |
| Sound power level Lwa  | dB(A)                     | 33   |
| Reference air flow rate  | m <sup>3</sup> /s         | 0.035  |
| Reference pressure differential                                | Pa                        | 50   |
| Specific input   | W/(m <sup>3</sup> /h)     | 0.27   |
| Control factor, time control                                   |                           | 0,95   |
| Declared maximum internal leakage rates                        | %                         | 2,22   |
| Declared maximum external leakage rates                        | %                         | 2.78   |
| Filter change indicator  |                           | Visual filter change indicator integrated in display of the remote control |
| Internet address for assembly and disassembly instructions     |                           | <a href="http://www.stiebel-eltron.com">www.stiebel-eltron.com</a>         |
| Annual power consumption in colder climates with time control  | kWh/a                     | 887  |
| Annual power consumption in average climates with time control | kWh/a                     | 350  |
| Annual power consumption in warmer climates with time control  | kWh/a                     | 305  |
| Annual heating savings in colder climates with time control    | kWh/a                     | 8237   |
| Annual heating savings in average climates with time control   | kWh/a                     | 4210   |
| Annual heating savings in warmer climates with time control    | kWh/a                     | 1904   |